


# ALLNET PCIe 10G X4 10G/5G/2,5G/1GBit Single Port PCIe LAN Ca





ALL0138v2-1-10G-TX is a PCI Express x4 single-port 10 Gigabit Ethernet network adapter is based on the Aquantia AQtion AQC107 chip solution. It is also compatible with PCIe x8 and x16 channels. A high-performance, five-rate NIC adapter that integrates PCIe, MAC, and PHY to provide power and space-efficient connectivity to client systems. The PCIe x4 universal interface gives this product great flexibility. The integrated PHY can be routed through Cat 6a at speeds up to 10 Gbps over a distance of 100 meters. It also supports 5 Gbps network connections over traditional Cat 5e or Cat 6 cabling.

The ALL0138v2-1-10G-TX is IEEE 802.3an & IEEE 802.3 bz compliant and enables 2.5GBASE-T, 5GBASE-T, 10GBASE-T, 1000BASE-T and 100BASE-TX transmission over 100m twisted pair cabling.

#### **Technical Details:**

| Hardware Specification | AQUANTIA-AQC107  |
|------------------------|--|
| Hardware Bus Type      | PCI Express 3.0 8.0 GT/s   |
| Bus Type               | PCIE-X4  |
| Physical Interface     | IEEE802.3u 100BASETX, IEEE802.3ab 1000BASEF,                     |
|                        | IEEE802.3an 10GBASETT, IEEE802.IQ VLANs, IEEE802.3x FlowControl, |
|                        | IEEE802.Ip Priority Queuing, IEEE 802.3azEEE                     |
| Indicators             | LED, 1-10G speed LED(Amber)                                      |
|                        |  |

#### www.allnet.de

ALLNET GmbH - Maistraße 2 - 82110 Germering - sales@allnet.de - 089 / 894 222 22 Errors and technical changes that serve the interests of progress or development of the product, are reserved.



| Network Port Type   | 10G RJ45  |
|---------------------|---|
| Full/half Duplex    | Self-adaptive   |
| Network Environment | 10G Ethernet  |
| Suits For           | PCI Express enabled PC, and with available PCI Express x4 slot                    |
|                     | Gen2.0 or higher (x8, x16)  |
| Support OS          | Windows®7, 8.x, 10  |
|                     | Windows Server®2008R2, 2012, 2016   |
|                     | Linux 2.6.x to 4.x  |
| Working Environment | Environment humidity: 20-80%RH  |
|                     | Working temperature:5° C~50° C  |
|                     | Storage temperature:-25° C~70° C  |
| Package Content     | 1x ALL0138v2-1-10G-TX Network Card<br>1x User guide<br>1x Screw<br>1x Case baffle |


### **Additional Images**





## www.allnet.de





### Accessories

 Part No.
 Name

 141149
 CommScope RUCKUS ZoneFlex R720 Dual Band 802.11ac 4x4:4 IEEE802.bz/Nbase-T

