

E1-Zoom-IP-Camera-Specifications			
	Model	E1 Zoom	
Hardware Features	Image Sensor	1/2.7" CMOS Sensor	
	Display Resolution	2560x1920 (5 Megapixels)	
	Lens	f=2.8-8mm Autofocus, F=1.6, with IR Cut	
	Optical Zoom	3X	
	Angle of View	Horizontal:	48° - 98°
		Vertical:	37° - 75°
	Pan/Tilt Angle	Horizontal:	355°
		Vertical:	50°
	Minimum Illumination	0 Lux (with IR Illuminator)	
	IR Distance	12m (40ft) (LED: 10pcs/14mil/850nm)	
	Dimension	Φ80x111mm	
	Weight	250g	
	Power Input	DC 5.0V/1A	
Interface	Power Interface		
	Micro SD Card Slot (Max. 128GB)		
	Built-in Microphone and Speaker		
	Reset Button		
Software Features	Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P	
	Image Compression	H.264	
	Maximal Frame Rate	20fps	
	Code Rate	1024Kbps ~ 4096Kbps (Default: 4096Kbps)	
	Audio	Two-way Audio	
	Maximal User Access	20 Users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)	
	Browser Supported	IE, Edge, Chrome, Firefox, Safari	
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android	
	Record Mode	Motion-triggered recording; scheduled recording	
	Alarm	Siren (customizable)	
Wireless Features	Works with	Google Assistant; Reolink Cloud *Available in some countries	
	Wireless Standard	IEEE 802.11a/b/g/n	
	Operating Frequency	2.4/5 GHz	
Other Parameters	Wireless Security	WPA-PSK/WPA2-PSK	
	Temperature	Operating Temperature:	-10°C~+55°C
		Storage Temperature:	-40°C~70°C
	Humidity	Operating Humidity:	20% ~ 85%
Storage Humidity:		10% ~ 90%	
Waterproof		No	
	Warranty	Limited Warranty	
2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/			