



## Construction Camera Bundle

# **BCC2000 Plus Datasheet**

## Features

1. HDR & FHD Time Lapse Video
2. Flexible Schedule Setup
3. 1-year Battery Life
4. Interchangeable Lens
5. Weather Resistant IPX5
6. Adjustable Clamp Mount
7. Extender Kit (AFB1000)

## Unique Selling Points

1. Connect to External Power
2. Simultaneous Record & Download \*1
3. 32 ft (10m) Ruggedized Cable
4. High Speed Data Transfer
5. Brinno Command Center (Windows Only) \*2
  - Start/ Stop recording
  - Preview camera frame
  - Change settings
  - Check battery & SD status

**Note:**

1. **Uses default file explorer to download files, no app required**
2. **Compatibility: Windows 7, 8, 8.1, & 10 with 64-bit OS.**  
**Up to date info at [brinno.com](http://brinno.com)**

## Package Contents

1. **Construction Camera Bundle BCC2000**
  - Time lapse camera: TLC2000
  - Construction power housing: ATH2000
  - Clamp mount kit: ACC1000
2. **Camera Extender Kit AFB1000**
  - Ruggedized USB-C Cable
  - Multi-task Dongle
  - Mounting Adapter

## Specifications

### BCC2000

#### ● Time Lapse Camera

|                       |  |
|-----------------------|--|
| Model No.             | <b>TLC2000</b>   |
| Resolution            | 1080P ( 1920 x 1080)   |
| Aperture              | F2.0   |
| Field of View         | 118°   |
| Capture Mode          | Time Lapse, Step Video, Stop Motion, Still   |
| LCD Screen            | 2.0" TFT LCD   |
| Storage               | microSD/ microSDHC/ microSDXC<br>(up to 128 GB, recommend a minimum of Class 10)* <sup>1</sup>           |
| Power Source          | 2 AA Batteries<br>DC IN 5V (USB-C connector)   |
| Operating Temperature | 32 °F ~ 113 °F (0 °C ~ 45 °C)  |
| Size (WxHxD)          | 2.4 x 2.8 x 1.7 in (60 x 70.6 x 42.4 mm)   |
| Weight                | 3.0 oz (87.5 g) (without battery)  |
| Package Contents      | Camera; 2 AA batteries; microSD card; USB-C cable;<br>Lens cover (front); Lens cover (rear); User manual |

\*Notes:

1.Support up to 128GB microSD card. For 64 or 128 GB microSD card, follow instruction on the LCD screen to format the card before using it the first time.

#### ● Construction Power Housing

|                  |  |
|------------------|--|
| Model No.        | <b>ATH2000</b>   |
| IP-Rating        | IPX5 (weather resistant)   |
| Battery Slot     | Up to 16 AA batteries<br>Micro USB (output 5V 2A)  |
| Exchangeable     | Kit lens cover   |
| Lens Cover       | Extension lens cover (for Brinno BCS lens)   |
| Size (WxHxD)     | 6.6 x 6.1 x 4.5 in (167x156x115.5 mm)  |
| Weight           | 14 oz (393 g)  |
| Package Contents | Construction power housing; Camera mounting adapter;<br>Battery slot; Extension lens cover; Desiccant; Screwdriver;<br>USB-C adapter; 2 Bungee cords |

## ● **Clamp Mount Kit**

|                         |   |
|-------------------------|---|
| Model No.               | <b>ACC1000</b>  |
| Camera Mount Screw      | ¼" (6mm)  |
| Clamping Range          | Tube: 0.4- 3.5 in (10 - 90 mm)<br>Flat surface: 0.04- 3.5 in (1 -90 mm)                           |
| Magic Arm Load Capacity | 6.6 lb (3 KG)   |
| Clamp Load Capacity     | 110 lb (50 KG) (without extension pole)   |
| Size (LxWxH)            | Folded: 8.2 x 3.7 x 1.5 in (209 x 94 x 39 mm)<br>Extended: 6.9 x 7.1 x 2.4 in (176 x 180 x 60 mm) |
| Weight                  | 26.5 oz (750 g) (with magic arm)  |
| Materials               | Camera Clamp: Stainless steel; Aluminum<br>Magic Arm: Stainless steel; Aluminum                   |
| Contents                | Camera clamp; Magic arm   |

## **AFB1000**

### ● **Ruggedized USB-C Cable**

|                |   |
|----------------|---|
| Specifications | USB-A Male to USB-C Male<br>Weather proofing Cap and Seal<br>UV Coating |
| Size (WxHxD)   | 32 ft (10m)   |
| Weight         | 15.2 oz (450 g)   |

### ● **Multi-task Dongle**

|              |   |
|--------------|---|
| Model No.    | ACB1000   |
| Output       | USB-C (to camera)   |
| Input        | USB-C (for USB-C cable)<br>Micro USB (for ATH2000 battery slot) |
| Size (WxHxD) | 1.85 x 1.09 x 0.35 in (47.1 x 27.9 x 9 mm)                      |
| Weight       | 0.33 oz (9.3 g)   |

### ● **Mounting Adapter**

|                |   |
|----------------|---|
| Specifications | Designed to install TLC2000 series camera with AFB1000 connected into ATH2000 housing |
| Size (WxHxD)   | 4.9 x 2.7 x 0.6 in (126 x 69 x 14.7 mm)   |
| Weight         | 1.14 oz (32.5 g)  |

## Certifications

### TLC2020

|               |      |
|---------------|------|
| <b>CE</b>     |      |
| <b>FCC</b>    |      |
| <b>BSMI</b>   | (TW) |
| <b>C-tick</b> | (AU) |
| <b>IC</b>     | (CA) |

## Shipping Info

### EAN Code

**BCC2000 Plus** 4712417431648

### Package Dimension

**Size (WxHxD)** 9.9 x 10.1 x 7.5 in (252 x 257 x 190 mm)

**Weight** 6.4 lb (2.9 kg)

### Master Carton Dimension

**Size (WxHxD)** 20.9 x 16.3 x 11.3 in (530 x 415 x 287 mm)

**Weight** 26 lb ( 11.8 kg) **(N.W)**  
28.2 lb ( 12.8 kg) **(G.W)**

**Units per carton** 4 pcs