

Xerox[®] Phaser[®] 6500 Color Printer and WorkCentre[®] 6505 Color Multifunction Printer The right colors, the easy way



Phaser[®] 6500 Color Printer and WorkCentre[®] 6505 Color Multifunction Printer

The right solution for today's pace of business. Your busy workteam needs a value-packed color device that gets the job done with the rare combination of outstanding print quality, unparalleled simplicity, and day-in, day-out dependability. Introducing the Phaser 6500 and WorkCentre 6505.



The colors your business needs

The Phaser 6500 color printer and WorkCentre 6505 color multifunction printer give your important documents a powerful, colorful boost.

- Outstanding print quality. A print resolution of up to 600 x 600 x 4 dpi makes your printed communications stand out and grab attention.
- True Adobe® PostScript® 3™. Count on consistently precise print jobs with bright, true colors and superior graphics.
- Advanced toner technology. Xerox-exclusive EA Toner uses particles engineered for uniform size and shape, producing superior image detail and line definition, and text that's sharp and clear.
- Always the right color. Pantone® Color approved solid-color simulations and Xerox color correction technology ensure results that match your expectations.

Ready to help

We designed the Phaser 6500 and WorkCentre 6505 as simple color devices that support single users and small workteams.

- **Print and go.** Work quickly with print speeds of up to 24 ppm for color and black-and-white (letter) or 23 ppm for color and black-and-white (A4).
- More productivity for more people. Connect and go, thanks to built-in networking and seamless compatibility with mixed-user environments, including PC, Macintosh and Linux.
- Easy management. With Xerox CentreWare®
 IS, remote device administration is handled
 with ease right from your computer's browser.
- Out of color toner? Our Run Black feature lets you continue printing with black until you can replace toner.
- **Total peace of mind.** Our standard one-year on-site warranty is backed by the industry-leading Xerox Total Satisfaction Guarantee.

Easy on your environment

From arrival to disposal, the Phaser 6500 and WorkCentre 6505 help you meet today's environmental challenges.

- Print more, use less. Whether you choose manual two-sided printing or upgrade to convenient automatic duplexing, you'll conserve paper for reduced costs and lower environmental impact.
- Toner-only cartridges. With minimal packaging, our toner-only cartridges allow for 80% less waste than comparable color devices, using integrated print cartridges.
- A perfect fit. Both devices feature a small footprint, which allows for easy integration within your work space, whether on your desk or in a shared location.
- The quiet partner. Engineered for extra-quiet operation to minimize impact on busy offices.
- Consolidate and save. The value-packed WorkCentre 6505 multifunction printer will save on energy and supplies costs by combining the functions of multiple devices into one.

Phaser® 6500 Quick Facts

- Print up to 24 ppm (letter) or 23 ppm (A4)
- 600 x 600 x 4 dpi
- Optional automatic two-sided printing*
- Powerful 400 MHz processor
- Robust 40,000 pages/month duty cycle
- 256 MB memory, expandable to 768 MB
- First page out time of 13 seconds color, 12 seconds black-and-white

* Standard on DN configuration







Productivity, accelerated. The WorkCentre 6505 color multifunction printer builds on the outstanding print performance found in the Phaser 6500, delivering a host of powerful productivity tools designed to make your daily office tasks more efficient than ever.



The WorkCentre 6505 includes an intuitive front panel for configuring device settings and programming jobs.



A 35-sheet automatic document feeder handles media sizes from 5.5×5.5 in. to 8.5×14 in.



A front-side USB port allows users to quickly print from or scan to any standard USB memory device.



Powerful scanning capabilities include Scan to Email, Network Scanning, Direct Scan to Applications including Optical Character Recognition, and Scan to USB memory device.



Standard copy features include ID Card Copy, N-up, auto fit, cloning, collate and more.



Send faxes from the network using LAN Fax, or take advantage of full walkup fax features such as speed dial, remote receive and fax broadcast.



A standard 533 MHz processor and 256 MB memory (expandable to 768 MB) let the WorkCentre 6505 easily handle a heavy workload — even a steady stream of pages with graphics, photos and charts.




Optional 250-sheet paper tray increases capacity to 500 sheets — enough to load a full ream of paper.



WorkCentre® 6505 Quick Facts

- Print up to 24 ppm (letter) or 23 ppm (A4)
- 600 x 600 x 4 dpi
- Optional automatic two-sided printing*
- Powerful 533 MHz processor
- Robust 40,000 pages/month duty cycle
- 256 MB memory, expandable to 768 MB
- First page out time of 12 seconds color, and black-and-white

* Standard on DN configuration



Phaser® 6500 and WorkCentre® 6505

		Phaser 6500N	Phaser 6500DN	WorkCentre 6505N	WorkCentre 6505DN	
Speed		Jp to 24 ppm color and black-and-white (Letter) / 23 ppm color and black-and-white (A4)				
Duty Cycle		Up to 40,000 pages / month ¹				
Paper Handling Paper input Standa		NA NA			Automatic Document Feeder (ADF): 35 sheets: Custom Sizes: 5.5 x 5.5 in. to 8.5 x 14 in. / 139.7 x 139.7 mm to 215.9 x 355.6 mm	
		Manual Feed Slot: 1 sheet; Custom sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm				
		Tray 1: 250 sheets; Custom sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm				
	Optional	Tray 2: 250 sheets; Custom sizes: 5.8 x 8.3 in. to 8.5 x 14 in. / 148 x 210 mm to 216 x 356 mm				
Paper output		150 sheets face down				
Automatic two-sided pri	nting	Optional	Standard	Optional	Standard	
Print First-page-out-time		As fast as 13 seconds color / 12 seconds black-and-white As fast as 12 seconds color / 12 seconds black-and-white			or / 12 seconds black-and-white	
Resolution (max)		Up to 600 x 600 x 4 dpi				
Processor		400 MHz		533 MHz	533 MHz	
Memory (std / max)		256 MB / 768 MB				
Connectivity		USB 2.0, 10/100/1000 Base-T Ethernet				
Page description languages		Adobe® PostScript® 3™, PCL® 6 emulation				
Print features Standard						
Print features	Standard	PANTONE® Color approved solid Overlays², Banner sheets², Draft		ıklet printing, Skip blank pages, Run bla	ack, Covers/Separators², Poster printing², Watermarks²,	
Print features	Standard Optional ³	Overlays ² , Banner sheets ² , Draft		klet printing, Skip blank pages, Run bla	ack, Covers/Separators², Poster printing², Watermarks²,	
Print features Copy First-copy-out-tir	Optional ³	Overlays ² , Banner sheets ² , Draft	t mode ²		ack, Covers/Separators ² , Poster printing ² , Watermarks ² ,	
	Optional ³	Overlays ² , Banner sheets ² , Draft Secure print, Proof print, Person	t mode ²		ack, Covers/Separators ² , Poster printing ² , Watermarks ² , lor / 13 seconds black-and-white	
Copy First-copy-out-tir	Optional ³	Overlays ² , Banner sheets ² , Draft	t mode ²	As fast as 20 seconds co 600 x 600 dpi 1 sided to 2 sided copyir		
Copy First-copy-out-tir Copy resolution	Optional ³	Overlays ² , Banner sheets ² , Draft Secure print, Proof print, Person	t mode ²	As fast as 20 seconds co 600 x 600 dpi 1 sided to 2 sided copyii Auto fit, Cloning, Collate 33.6 Kbps with MH/MR/ Lighter / darker, Polling, protection, Fax forwardii	olor / 13 seconds black-and-white ng ⁴ , Reduce/enlarge (25%-400%), N-up copying, , ID Card Copy, Edge erase MMR/JBIG/JPEG compression, Secure fax receive, Remote receive (with external phone), Junk fax	
Copy First-copy-out-tir Copy resolution Copy features Fax	Optional ³	Overlays², Banner sheets², Drafi Secure print, Proof print, Person NA	t mode ²	As fast as 20 seconds co 600 x 600 dpi 1 sided to 2 sided copyir Auto fit, Cloning, Collate 33.6 Kbps with MH/MR/ Lighter / darker, Polling, protection, Fax forwardir speed dials, 6 group dial Scan to Email (local add	olor / 13 seconds black-and-white ng4, Reduce/enlarge (25 % -400 %), N-up copying, ID Card Copy, Edge erase MMR/JBIG/JPEG compression, Secure fax receive, Remote receive (with external phone), Junk fax ng, Delay send, Broadcast, Address book (up to 200 Is), Resolution up to 400 x 400 dpi, LAN Fax (Send) Iress book or LDAP integration), Network Scanning Is (server or computer), Direct Scan to Applications	
Copy First-copy-out-tir Copy resolution Copy features Fax Fax features ⁵ Scan	Optional ³	Overlays ² , Banner sheets ² , Drafi Secure print, Proof print, Person NA NA	t mode ²	As fast as 20 seconds co 600 x 600 dpi 1 sided to 2 sided copyir Auto fit, Cloning, Collate 33.6 Kbps with MH/MR/ Lighter / darker, Polling, protection, Fax forwardir speed dials, 6 group dial Scan to Email (local add via FTP (server) and SMI including OCR, USB Mer	olor / 13 seconds black-and-white ng*, Reduce/enlarge (25 % -400 %), N-up copying, the ID Card Copy, Edge erase MMR/JBIG/JPEG compression, Secure fax receive, Remote receive (with external phone), Junk fax ng, Delay send, Broadcast, Address book (up to 200 (s), Resolution up to 400 x 400 dpi, LAN Fax (Send) liress book or LDAP integration), Network Scanning 8 (server or computer), Direct Scan to Applications mory Device	
Copy First-copy-out-tir Copy resolution Copy features Fax Fax features ⁵ Scan Scan destinations	Optional ³	Overlays², Banner sheets², Drafi Secure print, Proof print, Person NA NA NA	t mode ²	As fast as 20 seconds co 600 x 600 dpi 1 sided to 2 sided copyir Auto fit, Cloning, Collate 33.6 Kbps with MH/MR/ Lighter / darker, Polling, protection, Fax forwardii speed dials, 6 group dial Scan to Email (local add via FTP (server) and SMI including OCR, USB Mer Up to 1200 x 1200 dpi r PDF / JPEG / TIFF (single	olor / 13 seconds black-and-white Ing*, Reduce/enlarge (25%-400%), N-up copying, In D Card Copy, Edge erase MMR/JBIG/JPEG compression, Secure fax receive, Remote receive (with external phone), Junk fax Ing, Delay send, Broadcast, Address book (up to 200 Is), Resolution up to 400 x 400 dpi, LAN Fax (Send) Irress book or LDAP integration), Network Scanning Is (server or computer), Direct Scan to Applications Information (1988)	

¹ Monthly volume capacity expected in any one month. Not expected to be sustained on a regular basis; 2 Accessed via PCL driver; 3 Requires optional Productivity Kit with 512 MB memory; 4 requires DN model or optional duplex unit; 5 Analog phone line required

Device Management

CentreWare $^{\otimes}$ Internet Services, CentreWare Web, PrintingScout $^{\otimes}$, Email alerts

Print Drivers

Windows® XP, Vista, Server 2003, Server 2008, 7; Mac OS® version 10.5 and higher; Linux, Xerox Global Print Driver®, Xerox Mobile Express Driver™

Media Handling

Automatic Document Feeder**: 12.5 lb. Bond -45 lb. cover /50-125 gsm; Manual Feed Slot and Trays: 16 lb. bond -80 lb. cover /60-216 gsm; Media types: Plain paper, glossy, business cards, envelopes, labels, cardstock

Operating Environment

Temperature: Storage: -4° to 104° F / -20° to 40° C; Operating: 50° to 90° F / 10° to 32° C; Humidity: 10% to 85%; Sound pressure levels: 6500: Printing (Enhanced): 53 dB(A), Standby: 25 dB(A); 6505: Printing (Enhanced): 52 dB(A), Standby: 22 dB(A); Sound power levels: Printing (Enhanced): 6500: 67.3 dB(A), Standby: 38.6 dB(A); 6505: 66.3 dB(A), Standby: 36.5 dB(A); Warm-up time (from sleep mode): as fast as 31 seconds

Electrical

Power: 110-127 VAC, 50/60 Hz or 220-247 VAC, 50/60 Hz; Power consumption: 6500: Standby: 55 W, Printing: 375 W, Sleep: 15 W; 6505: Standby: 65 W, Printing: 425 W, Sleep: 18.4 W; ENERGY STAR® qualified

Dimensions (WxDxH)

 $6500N/DN:15.9\times16.75\times16.4$ in. / $403.5\times425.5\times415.6$ mm; Weight: 6500N:40 lbs / 18.2 kg; 6500DN:42.7 lbs / 19.4 kg; 250-sheet feeder: $15.75\times18\times4.2$ in. / $400\times457\times107$ mm; Weight: 9.7 lbs / 4.4 kg; $6505N/DN:16.9\times21.4\times23$ in. / $430\times544.2\times584.4$ mm; Weight: 6505N:62.5 lbs / 28.4 kg; 6505DN:65.1 lbs / 29.6 kg; 250-sheet feeder: $16.5\times20.4\times4.2$ in. / $419.2\times518\times107$ mm; Weight: 9.9 lbs / 4.5 kg

Certifications

FCC Part 15, Class B, FCC Part 686, UL 60950-1/CSA 60950-1-07, 2nd Edition, CE Mark applicable to Low Voltage Directive (2006/95/EC), EMC Directive (2004/108/EC), and R&TTE Directive (1999/5/EC) 6, GOST, NOM, GS Mark, Citrix Ready, Section 508 (compliant with minor exceptions), ENERGY STAR® qualified

SuppliesHigh-capacity Print Cartridges*:

Black: 3,000 std. pages	106R01597
Cyan: 2,500 std. pages	106R01594
Magenta: 2,500 std. pages	106R01595
Yellow: 2,500 std. pages	106R01596
Standard-capacity Print Cartridges*:	
Cyan: 1,000 std. pages	106R01591
Magenta: 1,000 std. pages	106R01592
Yellow: 1,000 std. pages	106R01593
Options	
250-sheet feeder for Phaser 6500	097S04070
250-sheet feeder for WorkCentre 6505	097S04264
Productivity Kit	097S04269
Duplex unit	097S04069
Wireless network adapter	
– N. America power converter	097S03740
– European power converter	097S03741

^{*} Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

UK power converter





















097S03742