

## Reolink-Duo-IP-Security-Camera-Specifications

|                                   | Model                  | Reolink Duo   |
|-----------------------------------|------------------------|---|
| <b>Video &amp; Audio</b>          | Image Sensor           | 1/3" CMOS Sensor  |
|                                   | Video Resolution       | 2560 x 1440 (4.0 Megapixel) at 15 frames/sec  |
|                                   | Video Format           | H.265   |
|                                   | Field of View          | Horizontal: 150°; Vertical: 44°   |
|                                   | Infrared Night Vision  | 30 meters (LED: 6pcs/20mil/850nm)   |
|                                   | Color Night Vision     | Spotlights: 8pcs/4.4W/6500K/440 lumens  |
|                                   | Digital Zoom           | 16X digital zoom  |
|                                   | Audio                  | Two-way audio   |
| <b>PIR Detection &amp; Alerts</b> | Smart Alarm            | PIR detection/human detection/vehicle detection   |
|                                   | PIR Detecting Distance | Adjustable up to 10m (33ft)   |
|                                   | PIR Detecting Angle    | 150° horizontal   |
|                                   | Audio Alert            | Customizable verbal alerts  |
|                                   | Recording              | Motion-triggered recording  |
|                                   | Other Alerts           | Instant email alerts and push notifications   |
| <b>Wireless</b>                   | Operating Frequency    | 2.4GHz/5GHz   |
|                                   | Wireless Standard      | IEEE 802.11a/b/g/n  |
|                                   | Wireless Security      | WPA-PSK/WPA2-PSK  |
| <b>Power</b>                      | Battery                | 10400mAh rechargeable battery (Battery life varies based on settings, usage & temperature)  |
|                                   | Solar                  | Reolink Solar Panel   |
|                                   | DC Power               | 5V/2A USB power adapter   |
| <b>Storage</b>                    | Local Storage          | Micro SD card slot (supports up to 128GB)   |
|                                   | Cloud Storage          | Supports Reolink Cloud (available in some countries)  |
| <b>Working Environment</b>        | Operating Temperature  | -10°C to 55°C (14°F to 131°F)   |
|                                   | Weather Resistance     | IP66 weatherproof   |
| <b>Size &amp; Weight</b>          | Size                   | 195 x 103 x 56 mm   |
|                                   | Weight                 | 720g  |
| <b>Warranty</b>                   | Limited Warranty       | 2-year limited warranty. For support, visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a> |