



19" IPC 4U-4452-TFT 19" rack with TFT display and keyboard/mousepad drawer

With its built-in TFT display and built-in keyboard/mouse drawer, the 4U-4452 TFT is ideal for servers and workstations in locations where there is no way for a 19" rack.

The Slim-DVD mounting can be removed in a few easy steps and enables a relaxed mounting of the Slim-DVD drive. Behind the lockable front door of the case are two hot-swap hard disk frames for either 2.5" or 3.5" drives, which also protects the external drives and USB ports against unauthorized access.

Specifications

| | |
|------------------------------|---|
| Motherboard | Mini ITX, mATX, µATX, ATX maximal motherboard size WxD: 305mm x 280mm, 12" x 11" |
| Max. drive bays | Slim-DVD: 1 2.5"/3.5" external Hot Swap: 2 2.5" internal: 2* 3.5" internal: 1* |
| Front connectors | USB 2.0: 2 |
| Cooling system | Internal: 2x 80mm (serial, Molex connector) Rear: 2x 60mm (optional) |
| Controls | Power-Button Reset-Button |
| LED | Power HDD activity |
| Power supply | ATX PSU |
| Material | 1.0-1.2mm Steel |
| Maximum CPU cooler height | 145mm |
| Maximum graphics card length | 280mm |
| Packing units | Shipping Unit: 1 Piece Pallet: 12 Pieces |
| Warranty | 24 Months |
| Article number | 88887287 |
| EAN-Code | 4260455644884 |
| Scope of delivery | Key Screw set VGA cable |
| Features | Front door lockable USB 2.0 internal as block connector Keyboard/Mouse with USB connector Keyboard Layout English 8.9" TFT display resolution max. 1024x600 (interpolates 1920x1080) TFT connector DB15 VGA |

*can vary by using several mounting options

Dimensions and Weight

| | Cage | Case | Package |
|--------|-------|-------|---------|
| Height | 177mm | 177mm | 305mm |
| Width | 428mm | 482mm | 565mm |
| Depth | 520mm | 555mm | 685mm |

Weight (net): 12.97kg
Weight (gross): 16.02kg

Power Supply

| Connector | Quantity | Max. Length |
|--------------------|----------|-------------|
| Mainboard 20+4Pin | - | - |
| P4 12V 4Pin | - | - |
| P4/EPS 4+4Pin | - | - |
| P8 12V 8Pin | - | - |
| PCI-Express 6+2Pin | - | - |
| PCI-Express 6Pin | - | - |
| IDE 4Pin | - | - |
| S-ATA | - | - |
| Floppy | - | - |
| RPM sensor cable | - | - |
| Fan Control | - | - |
| Fan: 120mm | - | - |

Without

Certification:

