


DIGITUS SFP+ 10G 3 m AOC cable

DN-81229
EAN 4016032460183



SFP+ 10G 3m AOC cable

Allnet, CISCO, Dell, D-Link, Edimax, Etherwan, Fortinet,

DIGITUS® SFP+ 10G AOC cables are the ideal connection between switches in the backbone area. The following data rates and applications are supported when using the SFP+ 10G AOC cables: 10G Ethernet (10.21 Gbps), 10G fibre channel (10.52 Gbps), 8G fibre channel (8.5 Gbps), 4G fibre channel (4.25 Gbps), 2G fibre channel (2.125 Gbps), 1G fibre channel (1.0625 Gbps), Gigabit Ethernet (1.25 Gbps), CPRI Option 2,3,5,6,7,8, OBSAI RP3x2, RP3x4, RPx8. The SFP+ 10G AOC cables are compatible with all leading switch manufacturers.

High bandwidth without delays or signal loss

- 3 m maximum distance
- 1.0625-10.52 Gbps supported data rate
- Supported applications: 10G Ethernet (10.21 Gbps), 10G fibre channel (10.52 Gbps), 8G fibre channel (8.5 Gbps), 4G fibre channel (4.25 Gbps), 2G fibre channel (2.125 Gbps), 1G fibre channel (1.0625 Gbps), Gigabit Ethernet (1.25 Gbps), CPRI Option 2,3,5,6,7,8, OBSAI RP3x2, RP3x4, RPx8

- Compatible brands: Allnet, CISCO, Dell, D-Link, Edimax, Etherwan, Fortinet, Intellinet, KTI Networks, Level One, Netgear, PLANET, Tenda, TP-Link, TRENDnet, ZyXEL, ZTE etc. compatible
- DDM/DOM support
- Temperature range: 0 to +70 °C
- Connectors: SFP+
- Power: +3.3 V supply voltage
- Power consumption: 0.5 W
- 850 nm wavelength multimode fibre
- Length: 3 m
- Connection: SFP+
- DDM Support: no
- Ethernet speed: 10 Gigabit

Package contents

- SFP+ 10G 3 m AOC cable
- Quick start guide

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	200	15.00	48.00	48.00	38.00	87,552.00
Packaging Unit Inside	1	0.08	26.00	26.00	2.00	1,352.00
Packaging Unit Single	1	0.08	26.00	26.00	2.00	1,352.00
Net single without Packaging	1	0.07	26.00	26.00	2.00	1,352.00