parted No warranty for the correctness of the information State: 10 03 2021

IPC 4U-40255





IPC 4U-40255

The IPC **4U-40255** is the perfect rack for a cost-effective server system. Due to the excellent material quality combined with the excellent workmanship, Inter-Tech has created the basis for an extremely variable case.

So offers the **IPC 4U-40255** the option of removing the mounting frame on both sides and thus installing up to six additional 5.25" external drives, up to 3x 5.25" external drives are available as standard. A maximum of 11x 3.5" or 4x 2.5" hard drives can be installed internally, depending on the configuration.

In addition, two 120mm and two 80mm fans reliably ensure optimal cooling.

Two easily accessible USB 3.0 front ports in the front and the lid with two snap-in closures complete the package.



IPC 4U-40255

Specifications

Motherboard Mini-ITX, mATX, µATX, ATX, SSI CEB, SSI EEB, eATX maximal motherboard size BxT: 305mm x 330mm, 12" x 13" Drive bays 5.25" external: 3* 3.5" internal: 11* 2.5" internal: 4* Front connectors USB 3.0: 2 Cooling system Front: 2x 120mm (included, Molex connector) 6x 40mm (optional, behind the 5.25"brackets) Rear: 2x 80mm (included, 3pin connector) Controls Power-Button Reset-Button **LED** Power **HDD Activity** 3x Network Activity ATX-/Redundant-PSU Power supply Material 1.0-1.2mm Steel Maximum CPU cooler height 150mm Maximum graphics card length 330mm Shipping unit: 1 piece Packing units Pallet: 15 pieces Warranty 24 Months Article number 88887304 4260455645935 EAN-Code Scope of delivery Screw Set Mounting rails for 3.5" hard drives Mounting frame for redundant power supplies **Features** 7 slot openings 2x 120mm and 2x 80mm fan included Up to 6x 40mm fan optional mountable Lid with snap lock

Dimensions and Weight

	Cage	Case	Package
Height	177.8mm	177.8mm	250mm
Width	433mm	485mm	560mm
Depth	550mm	595mm	735mm
	net): 11.46kg ross): 13.71		

ower Supply	L	
Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	4.
P8 12V 8Pin	-	41
PCI-Express 6+2Pin	4 100	UL
PCI-Express and	tho	
IDE 4Pin		-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

Certification: