

DIGITUS aluminum outlet strip with overload protection, 12 safety outlets, 2 x 2 m supply safety plug

DN-95405

EAN 4016032266433



Aluminum PDU, rackmountable, 12x safety outlet 2x 16A, 250VAC 50/60Hz, overload protection

The DIGITUS® power strips are the perfect solution for your network or server cabinet. In terms of power distribution, the PDU meets requirements of many applications in IT, network technology, laboratories as well as the home. The power strip can be mounted vertically in the rack. The PDU has 2 separate supply lines. An integrated overload protection per feed protects the connected loads from overload. Depending on the rack type, it is possible to mount the PDU with the taps facing right or left.

Safe and professional power supply with overload protection and 2 feeds

- 2 independent feeds
- Overload protection per feeder, interrupting capacity: 1000 A
- Vertical installation in the Rack
- Rotation of the outlets: 35°

- Housing: Aluminium
- Plastic components made of ABS UL-94V-0
- Input: 2 x plug Schuko CEE 7/7, 230 Vac / 16 A
- Output: 2 independent groups with 6 x Schuko DIN 49440 each, max. 16 A per output
- Supply line: 2 feeds, 2 x cable cross-section: 1.5 mm², length: 2 m
- Dimensions: 767.6 x 45 x 45 mm (HxWxD)
- Approvals: CE mark
- Scope of delivery: 1 power strip, 2 mounting brackets; 1 safety instructions
- Current: 16 A
- Input Plug: Schuko CEE7/7
- Installation: Rack 0U
- Outlets: Schuko CEE 7/3
- Phase: 1ph
- Power: 7,3 kVA
- Volts: 230 V

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	10	23.15	95.00	24.50	42.00	97,755.00
Packaging Unit Inside	1	2.32	9.30	80.00	7.00	5,208.00
Packaging Unit Single	1	2.32	9.30	80.00	7.00	5,208.00
Net single without Packaging	1	2.18	9.30	80.00	7.00	5,208.00

More images:



