

IPC 4U-4420



IPC 4U-4420

The **IPC 4U-4420** is the ideal case for a small and cheap server solution. With its excellent quality and finish, Inter-Tech established the basis for a very variable case.

The **IPC 4U-4420** offers the possibility to install maximal twenty 2.5" or 3.5" Hot-Swap HDDs, one Slim DVD external and three 2.5" or two 3.5" internal HDDs. The **IPC 4U-4420** has five fans as standard, from which three 120mm are mounted directly at the back of the drive brackets. In addition, two 80mm fans at the back ensure a reliable and optimal cooling.

Additional extras like the reusable and perforated slot brackets and the lid with the snap lock round off the picture.

Inter-Tech Elektronik Handels GmbH

IPC 4U-4420

Specifications

Motherboard Mini ITX, µATX, ATX, eATX, SSI EEB

maximal motherboard size WxD: 305mm x 345mm, 12" x 13.5"

20x 2.5" or 3.5" Hot-Swap (max. 12G) Drive Bays 1x drive bay Slim DVD for 1x Slim DVD or 1x 2.5"

internal hard drive

2x drive bays 3.5" for 1x 3.5" or 1x 2.5" internal

hard drive

Front Connectors USB 3.0: 2

Cooling System Internal: 3x 120mm (included, Molex connector)

Rear: 2x 80mm

(included, 3pin (4pin connector)) Controls Power-Button

Reset-Button **LED** Power

HDD Activity

3x Network Activity

Alert

Power Supply ATX / Redundant PSU

Material 1.0/1.2mm Steel

Maximum CPU cooler height 155mm

Maximum graphics card length 345mm Packing Units Shipping Unit: 1 piece

Pallet: 12 pieces

Guarantee and Warranty Case 24 Months Warranty

Article Number 88887121

4260133126428 EAN-Code

Scope of Delivery Screw set Mounting bracket for ATX (preassembled), 4U

redundant and 3U triple redundant PSU

Adapter for 2U PSU + optional 80mm fan bracket

Mounting bracket for diverse PSU

Assembly tool

Features 3x 120mm and 2x 80mm fan included

Drive brackets removable

USB 3.0 as block connector

7x perforated slot bracket

Snap locks

S-ATA/SAS Hot-Swap backplane with SFF-8087 socket¹

¹ The backplane is only compatible with a SAS-Controller with SFF-8087 connector. In operation with SATA-Controllers, please order the optional SFF8087 cross-over cables (Art.-No.: 88885237) in right quantity.



IPC 4U-4420

Dimensions and Weight Cage Case Package Height 178mm 178mm 240mm Width 560mm 433mm 481mm Depth 650mm 688mm 830mm Weight (net): 15.10kg Weight (gross): 18.00kg

ower Supply	_	
Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	4.
P8 12V 8Pin	-	_ 4
PCI-Express 6+2Pin	4160	
PCI-Express in	tho	
IDE 4Pin	tho	-
S-ATA		-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	_	_

Certification: