





Note: It covers 7,200 ft<sup>2</sup> with 3-pack, 5,500 ft<sup>2</sup> with 2-pack, and 2,900 ft<sup>2</sup> with 1-pack.








# The Best Performance & Coverage

Thanks to the greenfield 6 GHz band with more spectrums, it benefits the backhaul performance between Deco units, bringing the most stable and strongest network, covering every corner of your home. Thus, it also improves the overall WiFi performance of all non-6E devices.







### Intelligent Networking for a Smarter Home

Deco uses its custom algorithms to automate the connections on your network, ensuring the strongest possible signals at all times.§

Learn more about Al-Driven Mesh >>



### HomeShield Protect Your Network and Everything on It

TP-Link's premium security services keep your home network safe with cutting-edge features for network and IoT protection.\*\*



Detect cyber threats to keep your privacy and connected devices well protected. · Real-Time IoT Protection · Malicious Site Blocker Intrusion Prevention
 Home Network Scanner



Manage online time and block inappropriate content to keep families healthy online. · User Profile by Age · Content Filter - Redtime Time Rewards



Prioritize your bandwidth needs to get a faster networking experience. · Device Priority



network better. Internet User Overview Online Time Analysis Browser History Analysis End Device Statistics

### Control Anyway You Want



#### Easy Management

Manage your WiFi at home or away on the Deco app. See every connected device, prioritize your own, and set up a guest network.



#### Voice Control

Pair with Alexa to control Deco XE75 with simple voice commands. Enjoy the convenient life.





#### All Decos Work Together

Deco XE75 is compatible with every other Deco model to form a Mesh network. Expand Mesh WiFi coverage anytime by adding more Decos.



<sup>†</sup>Maximum wireless signal rates are the physical rates derived from IEEE Standard 802.11 specifications. Actual wireless data throughput, wireless coverage, and quantity of connected devices are not guaranteed and will vary as a result of network conditions, client limitations, and environmental factors, including building materials, obstacles, volume and density of traffic, and client location.

<sup>‡</sup>Clients need to support 802.11k/v/r and may require additional setup. Performance may vary depending on the client device.

<sup>Δ</sup>Use of Wi-Fi 6, Wi-Fi 6E, and other features including OFDMA, MU-MIMO, 1024-QAM, and BSS Color require clients to also support the corresponding features. The 160 MHz bandwidth may be unavailable in the 5 GHz band in some regions/countries due to regulatory restrictions.

\*HomeShield includes the Free Basic Plan. Fees apply for the Pro Plan. Visit tp-link.com/homeshield for more information.

\*\*WiFi 6E allows for 7 (3 for European Union Member states) additional 160 MHz channels, offering up to 1,200 MHz (480 MHz for European Union Member states) of additional spectrum for 6 GHz WiFi.

\*\*\*Deco XE75 works with all Internet Service Providers and is 100% backward compatible with all WiFi generations and devices.

## SPECIFICATIONS

WIRELESS		
Standards	Wi-Fi 6E IEEE 802.11ax 6 GHz IEEE 802.11ax/ac/n/a 5 GHz IEEE 802.11ax/n/b/g 2.4 GHz	
WiFi Speeds	AXE5400 6 GHz: 2402 Mbps (802.11ax, HE160) 5 GHz: 2402 Mbps (802.11ax, HE160) 2.4 GHz: 574 Mbps (802.11ax)	
WiFi Range	4-7+ Bedroom Houses (3-pack)     3-5 Bedroom Houses (2-pack)     1-3 Bedroom Houses (1-pack)     TP-Link Mesh Technology     Optional Ethernet backhaul work together to link Deco units to     provide seamless coverage     Al-Driven Mesh     Intelligently learns the network environment to provide ideal Wi-Fi     unique to your home	
	High-Gain Antennas (Internal)     Multiple antennas form a signal-boosting array to cover more     directions and large areas     Tri-Band     A newly-opened 6 GHz band brings more bandwidth and faster     speeds     Beamforming     Concentrates wireless signal strength towards clients to expand     WiFi range	
WiFi Capacity	Very High         Tri-Band         Distribute devices to different bands for optimal performance         2×2 MU-MIMO         Simultaneously communicates with multiple MU-MIMO clients         OFDMA         Very Market and the state with a WE and the METER and the state with a WE and the state withe	
Working Modes	Simultaneously communicates with multiple WiFi 6 clients 6 Streams More than enough bandwidth for connected devices Router Mode Access Point Mode	
5	Access Point Mode	
HARDWARE		
Processor	1.7 GHz Quad-Core CPU	
Ethernet Ports	3× Gigabit Ports *Per Deco Unit Supports WAN/LAN auto-sensing	
Buttons	Reset Button	
SECURITY		
WiFi Encryption	WPA-Personal WPA2-Personal WPA3-Personal	
Network Security	SPI Firewall Access Control HomeShield Security Real-Time IoT Protection Malicious Site Blocker Intrusion Prevention System DDoS Attack Prevention Home Network Scanner	
Guest Network	1× 6 GHz Guest Network 1× 5 GHz Guest Network 1× 2.4 GHz Guest Network	
SOFTWARE		
Protocols	IPv4 IPv6	
Service Kits	HomeShield	

SOFTWARE	
Parental Controls	HomeShield Parental Controls Custom Profiles Professional Content Filter Library Family Time Bedtime Off Time Time Rewards Family Online Time Ranking Pause the Internet Weekly and Monthly Reports
WAN Types	Dynamic IP Static IP PPPoE PPTP L2TP
Quality of Service	HomeShield QoS QoS by Device
Cloud Service	OTA Firmware Upgrade TP-Link ID DDNS
NAT Forwarding	Port Forwarding UPnP
IPTV	IGMP Proxy IGMP Snooping Bridge Tag VLAN
DHCP	Address Reservation DHCP Client List Server
DDNS	TP-Link
Management	Deco Арр
PHYSICAL	
Dimensions (W×D×H)	4.1 × 4.1 × 6.7 in (105 × 105 × 169 mm)
Package Contents	Deco XE75 (3-pack) 3 Deco XE75 units 1 RJ45 Ethernet cable 3 Power adapters 1 Quick Installation Guide Deco XE75 (2-pack) 2 Deco XE75 units 1 RJ45 Ethernet cable 2 Power adapters 1 Quick Installation Guide Deco XE75 (1-pack) 1 Deco XE75 units 1 RJ45 Ethernet cable 1 Power adapters 1 Quick Installation Guide
OTHERS	
Certifications	CE, FCC, RoHS
Environment	Operating Temperature: 0°C~40°C (32 °F~104 °F) Storage Temperature: -40°C~60°C (-40 °F~140 °F) Operating Humidity: 10%-90% RH Storage Humidity: 5%~90% RH
TEST DATA	
WiFi Transmission Power	CE: <20 dBm (2.4 GHz) <23 dBm (5 GHz) <23 dBm (6 GHz) FCC: <30 dBm (2.4 GHz) <30 dBm(5 GHz) <30 dBm(6 GHz)

<sup>†</sup>Maximum wireless signal rates are the physical rates derived from IEEE Standard 802.11 specifications. Actual wireless data throughput, wireless coverage, and quantity of connected devices are not guaranteed and will vary as a result of network conditions, client limitations, and environmental factors, including building materials, obstacles, volume and density of traffic, and client location.

<sup>‡</sup>Clients need to support 802.11k/v/r and may require additional setup. Performance may vary depending on the client device.

<sup>Δ</sup>Use of Wi-Fi 6, Wi-Fi 6E, and other features including OFDMA, MU-MIMO, 1024-QAM, and BSS Color require clients to also support the corresponding features. The 160 MHz bandwidth may be unavailable in the 5 GHz band in some regions/countries due to regulatory restrictions.

\*HomeShield includes the Free Basic Plan. Fees apply for the Pro Plan. Visit tp-link.com/homeshield for more information.

\*\*WiFi 6E allows for 7 (3 for European Union Member states) additional 160 MHz channels, offering up to 1,200 MHz (480 MHz for European Union Member states) of additional spectrum for 6 GHz WiFi.

\*\*\*Deco XE75 works with all Internet Service Providers and is 100% backward compatible with all WiFi generations and devices.