

# ThinkVision P27q-30

# Multi-featured for multitasking seamlessly. Powered to do more.

For professionals working in various fields and multi-taskers with high productivity who want extra valued features for efficiency and productivity - the Lenovo ThinkVision P27g-30 Monitor is the right choice to amplify your performance at work. The large 27-inch QHD resolution IPS display makes it convenient to accommodate multiple windows without compromising clarity. Constructed with a 4-side NearEdgeless design, you get more screens without taking more space. Get vibrant images from any angle with 99% sRGB, 99% BT.709, and 95% DCI-P3; together with Avg. Delta E<2 color accuracy. Not just that, the HDR10 support delivers a realistic visual experience with video content. Expand the potential of your productivity by seamlessly connecting with external devices through a versatile range of connectors, including HDMI 2.0, DP 1.4, and USB ports. Experience a fast 'plug-and-play' multi-screen experience with daisy chain (DP output). The Natural Low Blue Light technology reduces eye strain without color distortion so that you get long durations of screen time to get work done without any discomfort. The ergonomically designed stand comes equipped with tilt, lift, pivot, and swivel function - allowing you to adjust the monitor to the most comfortable height and angle for your viewing pleasure.

### FEATURES OF THINKVISION P27q-30 MONITOR



## USB Type-A\* USB Type-A USB Type-A USB Type-A USB Type-A USB Type-A USB Type-A



#### Expand your point of view

The ThinkVision P27q-30 monitor flaunts a 27-inch 2560 x 1440 QHD resolution IPS (In-Plane Switching) display that exhibits crisp visuals from end-to-end, from nearly any corner with color accuracy and excellent contrast ratio even from wide-viewing angles. Built with a 4-side NearEdgeless design, staying focused is easy while having more screen and less noise. Get a stunningly vivid color performance with 99% sRGB, 99% BT.709, and 95% DCI-P3; together with Avg. Delta E<2 color accuracy. Additionally, view real-like HDR video content with superior HDR10 support.

#### **Productivity with flexibility**

The ThinkVision P27q-30 monitor lets you double your multitasking capabilities with the advantage of a fast multi-screen experience. Plug-and-play an additional screen to enjoy dual screens via daisy chain (DP output). The ThinkVision P27q-30 monitor lets you unleash new possibilities by connecting multiple external devices with an extensive variety of connectors that include HDMI 2.0, DP 1.4, and an array of USB ports. Not just that, get an extended monitor function with ThinkVision VoIP Stack\* (ThinkVision MC60 Monitor Webcam and MS30 Monitor Soundbar).

#### Built for convenience, with care

The ThinkVision P27q-30 monitor gives you seamless control with its simplified cable management, easy control with the joystick, and easy-to-use OSD. Now complete jobs that require long hours of work comfortably without affecting your eyes' health or experiencing eye strain with the Natural Low Blue Light technology that automatically reduces harmful blue light without any color distortion. The ergonomically designed stand's extended lift and swivel ranges, now you can easily adjust the monitor to the height and angle that best lets you work comfortably. Because we aim to find the best solutions for you - without affecting the environment, the ThinkVision P27q-30 is made TCO 9.0 compliant, and is boxed in a paper package with pulp cushion.

# ThinkVision P27q-30

### **DISPLAY**

Panel Size 27-inch

Screen Dimensions (W x H. mm) 608.6 mm x 348.6 mm

Panel Type 4-side NearEdgeless In-Plane Switching

Active Area 596.7 mm x 335.7 mm

Backlight WLED

Aspect Ratio 16:9

Resolution 2560 x 1440

Pixel Pitch 0.2331 mm x 0.2331 mm

Dot/Pixel Per Inch (DPI/PPI) 109

Viewing Angle (H x V @ CR 10:1) 178° / 178°

Response Time 4ms (Extreme Mode). 6ms (Normal Mode), 14ms (Off Mode)

**Refresh Rate** 60 Hz

**Brightness (Typical)** 350 cd/m<sup>2</sup>

**Contrast Ratio (Typical)** 1000:1

Dynamic Contrast Ratio (Typical) 3M·1

Color Gamut 99% sRGB, 99% BT.709, 95% DCI-P3

**Color Support (Typical)** 1.07 Billion

Color Depth 10-bit (8+FRC)

HDR Compliance Yes (HDR 10 Decoding)

Anti-Glare Yes

### CONNECTIVITY

Video Signal 1 x HDMI 2.0 1 x DP 1.4 1 x DP Out

Audio Signal 1 x Audio Out (3.5 mm)

**USB Hub** Yes

USB Upstream 1 x USB 3.2 Gen1<sup>1</sup> (by USB Type-B)

**USB** Downstream 4 x USB 3.2 Gen1<sup>1</sup> (1 x BC 1.2)

### MULTIMEDIA

**Factory Calibration** 

Yes (Avg. Delta E<2)

Lenovo ThinkColour

Natural Low Blue Light

Software

Yes

Modular Camera/Speaker Support Yes (Optional Support<sup>2</sup>)

(Lenovo Display Control Center)<sup>3</sup>

SPECIAL FEATURES

Yes (100 x 100 mm)

Bezel Width (Side) 2.0 mm

Size Packed (D x H x W) (mm/inch) 148.0 x 525.0 x 690.0 mm 5.83 x 20.67 x 27.17 inches

Size Unpacked w/ Stand (Lowest Position)  $(D \times H \times W) (mm/inch)$ 204.5 x 380.3 x 611.9 mm 8.05 x 14.97 x 24.09 inches

Size Unpacked w/ Stand (Highest Position) (D x H x W) (mm/inch) 204.5 x 535.3 x 611.9 mm 8.05 x 21.07 x 24.09 inches

Size Unpacked w/o Stand (Head Only)  $(D \times H \times W)$  (mm/inch) 48 0 x 353 4 x 611 9 mm 189 x 13 91 x 24 09 inches

Weight Packed (kg/lb) 10.0 kg / 22.1 lbs.

Weight Unpacked (kg/lb) 6.8 kg / 15.0 lbs.

Weight (Monitor Head Only) (kg/lb) 4.7 kg / 10.4 lbs.

### WHAT'S IN THE BOX

Monitor with Stand Yes

Power Cable 1 x Power Cable (1.8m)

DP Cable (Cable Length) 1 x DP 1.4 Cable (1.8m)

USB Cable 1 x USB Type-A to Type-B Cable (1.8m)

**Factory Calibration Report** Yes

**Quick Setup Guide** Yes

### CERTIFICATION

**ENERGY STAR Certification** Yes

CCC Yes

тсо Yes

> TCO Edge Yes

EPEAT Gold

RoHS (EU 2011/65/EU) Yes

Windows Certification Windows 10, Windows 11

**China Energy Efficiency Standard** Tier 2

TÜV Rheinland Eve Comfort Yes

**TÜV Low Blue Light** (Hardware Solution) Yes

**Eyesafe Display Certification** Ves







<sup>1</sup> Depending on many factors such as the processing capability of peripheral devices, file attributes, and other factors related to system configuration and operating environments, the actual transfer rate using the various USB connectors on this device will vary and is typically slower than the data rates as defined by the respective USB specifications: 5 Gbit/s for USB 3.2 Gen 1; 10 Gbit/s for USB 3.2 Gen 2 & 20 Gbit/s for USB 3.2 Gen2x2. <sup>2</sup> Compatible with ThinkVision VoIP Stack MC60 Monitor Webcam and MS30 Monitor Soundbar.

<sup>3</sup> This software can only be used with Windows 10 & Windows 11.

© 2022 Lenovo. All rights reserved. These products are available while supplies last. Prices shown are subject to change without notice. For any questions concerning price, please contact your Lenovo Account Executive. Lenovo is not responsible for photographic or typographic errors. Warranty: For a copy of applicable warranties, write to: Warranty Information, 500 Park Offices Drive, RTP, NC 27709, U.S.A, Attn: Dept. ZPYA/B600. Lenovo makes no representation or warranty regarding third-party products or services. Trademarks: Lenovo, the Lenovo logo, Rescue and Recovery, ThinkPad, ThinkCentre, ThinkStation, ThinkVantage, ThinkVision, and ThinkColour are trademarks or registered trademarks of Lenovo. Microsoft, Windows, and Vista are registered trademarks of Microsoft Corporation. Intel, the Intel logo, Intel Inside, Intel Core, and Core Inside are trademarks of Intel Corporation. in the U.S. and/or other countries. Other company, product, and service names may be trademarks or service marks of others.

Lift (Max. Range) 155 mm Pivot

POWFR

23W / 68W

< 0.5W

< 0.3W

Internal

-5°/23.5°

+45° / -45°

Yes

(Pon/ETEC)

20W / 60kWh

Power Supply

Smart Power

Voltage Required

AC 100 to 240 V (50-60 Hz)

MECHANICAL

Tilt Angle (Front / Back)

Swivel Angle (Left / Right)

Power Consumption (Typ. / Max.)

Power Consumption Sleep/Off Mode

**Power Consumption Switch-Off Mode** 

**ENERGY STAR Power Consumption** 

-90°/90°

VESA Mount Capability

Kensington Lock Slot

Yes

**Cable Management** Yes

**Bezel Color** Black

Bezel Width (Top / Bottom) 2.0 / 2.0 mm