



19" Intelligent 8-Port PDU

19" Rackmountable Intelligent Power Distribution Unit; Monitors Power, Temperature and Humidity

Part No.: **163682**

EAN-13: 0766623163682 | UPC: 766623163682

The Intellinet Network Solutions 19" Intelligent 8 Port PDU provides your system-critical devices with steady power, monitors current-voltage levels and keeps track of environmental temperature and humidity levels. A simple web interface enables the systems administrator to set thresholds for the safety of your valuable I.T. equipment.

Features:

- Eight-port, IEC320 C13 power output with total current of 16 A
- Displays total delivered power in voltage and watts
- Built-in temperature and humidity sensor monitors the operating environment
- Embedded technology, supports Java and web browsing
- Customizable Warning and Overload alarms
- Power-outlet delay-time configurable to prevent the possibility of a power surge to the integral power supply
- Power cycle of each port via web interface
- LED indicates power-supply condition of each power outlet
- Digital display shows real-time value of voltage and current, IP address, or temperature and humidity
- Built-in lightning-protection circuit and voltage-surge circuit
- Fanless design for silent operation
- Three-Year Warranty

Specifications:

Certifications

- FCC
- CE

General

- Power input: one IEC320 C20

For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Power outputs: eight IEC320 C13
- LAN connection: one RJ45 port

Technical

- Voltage input: 90-240 V 50/60 Hz
- Voltage output: 90-240 V 50/60 Hz
- Voltage measurement range: 90-264 VAC increment of 1 V
- Current measurement range: 0-20 A increment of 0.1 A
- Temperature measurement range: 0° - 50°C (32° - 122°F) increment of 1°C (1°F)
- Humidity measurement range: 20% - 90% increment of 1%

Physical

- Dimensions (D x W x H): 119.5 x 442 x 44.5 mm (4.69 x 17.4 x 1.75 in.)
- Net weight: 1.6 kg (4.54 lbs.)
- Gross weight: 2.38 kg (5.25 lbs.)
- Metal housing
- Flammability: Tested and rated in accordance with UL 94 V-0

Package Contents

- Intelligent 8-Port PDU
- 19" rackmount brackets
- Power cable C19 to C20
- Manual on CD



C13 Output



C20 Input

