

DIGITUS 4K HDMI Splitter, 1x16

DS-45328
EAN 4016032479994



4K HDMI Splitter, 1x16 4K/60Hz, 18Gbps, HDR, Downscaling, EDID

The DIGITUS® 4K HDMI Splitter, 1x16 distributes an AV signal onto 16 screens in UHD resolution (4K/60Hz) Thanks to the down-scaling function, no screen will remain black if for example a 4K signal needs to be output simultaneously on 4K and Full HD monitors. The splitter also offers the option of EDID management, different modes can be individually configured via the changeover switch.

Distributes an HDMI signal onto 16 screens in UHD resolution (4K/60Hz)

- Supports 4K2K/60Hz (HDR, 4:4:4)
- Video bandwidth: 18 Gbps
- Down-scaling function (4K -> 1080p) - Mixed operation of Full HD + 4K screen possible
- EDID management changeover switch
- HDMI 2.0
- HDCP 2.2 / 1.4
- Supports High Dynamic Range (HDR)
- Supports Deep Color (36-bit), 12 per channel
- Supports compressed audio formats such as LPCM
- Supports uncompressed audio formats such as DTS, Dolby Digital
- 17x Status LED
- Input:
- 1x HDMI jack (4K/60Hz)
- Output:
- 16x HDMI jack (4K/60Hz)
- Operating temperature: 0-70°
- Power consumption: approx. 12W
- Housing: Metal
- Dimensions: L 10.9 x W 25.7 x H 2.3 cm
- Color: black
- Supports 4K2K/60Hz (HDR, 4:4:4), Video bandwidth: 18 Gbps, Down-scaling function (4K -> 1080p) - Mixed operation of Full HD + 4K screen possible, EDID management changeover switch, HDMI 2.0, HDCP 2.2 / 1.4, Supports High Dynamic Range (HDR), Supports Deep Color (36-bit), 12 per channel, Supports compressed audio formats such as LPCM, Supports uncompressed

- audio formats such as DTS, Dolby Digital, 17x Status LED, Input: 1x HDMI jack (4K/60Hz), Output: 16x HDMI jack (4K/60Hz), Operating temperature: 0-70°, Power consumption: approx. 12W, Housing: Metal, Dimensions: L 10.9 x W 25.7 x H 2.3 cm, Color: black, , ,
- Supports 4K2K/60Hz (HDR, 4:4:4), Video bandwidth: 18 Gbps, Down-scaling function (4K -> 1080p) - Mixed operation of Full HD + 4K screen possible, EDID management changeover switch, HDMI 2.0, HDCP 2.2 / 1.4, Supports High Dynamic Range (HDR), Supports Deep Color (36-bit), 12 per channel, Supports compressed audio formats such as LPCM, Supports uncompressed audio formats such as DTS, Dolby Digital, 17x Status LED, Input: 1x HDMI jack (4K/60Hz), Output: 16x HDMI jack (4K/60Hz), Operating temperature: 0-70°, Power consumption: approx. 12W, Housing: Metal, Dimensions: L 10.9 x W 25.7 x H 2.3 cm, Color: black, , ,
- Supports 4K2K/60Hz (HDR, 4:4:4), Video bandwidth: 18 Gbps, Down-scaling function (4K -> 1080p) - Mixed operation of Full HD + 4K screen possible, EDID management changeover switch, HDMI 2.0, HDCP 2.2 / 1.4, Supports High Dynamic Range (HDR), Supports Deep Color (36-bit), 12 per channel, Supports compressed audio formats such as LPCM, Supports uncompressed audio formats such as DTS, Dolby Digital, 17x Status LED, Input: 1x HDMI jack (4K/60Hz), Output: 16x HDMI jack (4K/60Hz), Operating temperature: 0-70°, Power consumption: approx. 12W, Housing: Metal, Dimensions: L 10.9 x W 25.7 x H 2.3 cm, Color: black, , ,

Package contents

- 1x HDMI splitter
- 1x Power adapter (12V/2A, 1.15 m)
- 1x QIG

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm ³ |
| Packaging Unit Carton | 20 | 22.00 | 58.50 | 60.00 | 26.00 | 91,260.00 |
| Packaging Unit Inside | 1 | 1.10 | 23.80 | 29.20 | 5.50 | 3,822.28 |
| Packaging Unit Single | 1 | 1.10 | 23.80 | 29.20 | 5.50 | 3,822.28 |
| Net single without Packaging | 1 | 0.73 | 11.00 | 25.70 | 2.30 | 650.20 |

More images:

