

10/100 Mbps Multi Mode Fiber Media Converter SC 2 km

## Product ID: ET90110SC2



The ET90110SC2 10/100 Mbps Multimode Fiber Media Converter SC (2 km) lets you extend a Fast Ethernet network (10/100Mbps) over multimode fiber, at distances up to 2 km (1.2 miles).

A cost-effective solution for connecting a 10/100 Mbps Ethernet (10/100Base-T) network to remote network segments over a 100Base-FX fiber backbone, the media converter is designed to offer a durable and convenient Ethernet-to-fiber solution, featuring an all-steel chassis, and a simple plug-and-play installation with minimal configuration required.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

## **Certifications, Reports and Compatibility**













## **Applications**

- Provides connectivity to a user or network segment that is in an isolated area of a large complex or in another building altogether
- Perfect for secure environments required by government agencies where EMI is not acceptable
- Connect traffic control/monitoring systems at extreme distances to the main office
- Extend network connectivity to remote areas of stadiums, auditoriums or other venues
- Converts 10/100Base-T Ethernet to 100Base-FX fiber optic signals over multimode fiber cable



## **Features**

- · Advanced features include Link-loss forwarding, remote status monitoring, two frame lengths
- Supports a maximum fiber cable length of 2 km
- Supports full or half-duplex operation
- Easy to use and install

Н	aı	rd	w	а	re

Warranty 2 Years

PoE No

WDM No

Industry Standards IEEE802.3 (10BASE-T)

IEEE802.3u (100BASE-TX)

IEEE802.3u (100BASE-FX)

**Performance** 

Maximum Data Transfer Rate

200 Mbps (Full Duplex Mode)

Max Transfer Distance

2 km (1.2 mi)

Type

Multi Mode

Wavelength

1310nm

Fiber Operating Mode

Half/Full-Duplex

Auto MDIX

Yes

Connector(s)

Local Unit Connectors

1 - Fiber Optic SC Duplex

1 - RJ-45

Power

Power Source AC Adapter Included

Input Voltage 100 - 240 AC



Input Current 0.48A

Output Voltage 12V DC

Output Current 1.6 A

Center Tip Polarity Positive

Plug Type M

**Environmental** 

Operating Temperature 0C to 60C (32F to 140F)

Storage Temperature -10C to 70C (14F to 158F)

Humidity 10~90% RH

Physical Characteristics

Color Black

Material Steel

Product Length 6.3 in [16.0 cm]

Product Width 3.5 in [8.8 cm]

Product Height 0.9 in [2.3 cm]

Weight of Product 13.8 oz [390.0 g]

Packaging Information

Package Quantity 1

Package Length 9.2 in [23.3 cm]

Package Width 7.5 in [19.0 cm]

Package Height 3.0 in [7.7 cm]

Shipping (Package) 1.7 lb [0.8 kg]

Weight

What's in the Box

Included in Package 1 - Fiber Media Converter

1 - Universal power adapter: comes ready for NA/EU/UK only when you buy in NA/EU/UK; comes ready for Australia and New



Zealand only when you buy in Australia and New Zealand

- 1 Grounding Screw
- 1 Instruction Manual

\*Product appearance and specifications are subject to change without notice.