



APC Smart-UPS SMT1500IC Noodstroomvoeding - 8x C13, USB, SmartConnect, 1500VA

Merk : APC

Artikelcode: SMT1500IC

Productnaam : Smart-UPS SMT1500IC Noodstroomvoeding
- 8x C13, USB, SmartConnect, 1500VA

APC Smart-UPS SMT1500IC Noodstroomvoeding - 8x C13, USB, SmartConnect, 1500VA

APC Smart-UPS SMT1500IC Noodstroomvoeding - 8x C13, USB, SmartConnect, 1500VA. UPS-topologie: Line-interactive, Output power capacity: 1,5 kVA, Uitgangsvermogen: 1000 W. Stopcontacttypes: C13 stekker, IEC Jumpers, Stekker: C14 stekker, Aantal AC uitgangen: 8 AC-uitgang(en). Batterijtechnologie: Sealed Lead Acid (VRLA), Acculevensduur (max): 5 jaar, Accu/Batterij oplaadtijd: 3 uur. Vormfactor: Mini Tower, Kleur van het product: Zwart, Snoerlengte: 1,83 m. Breedte: 171 mm, Diepte: 439 mm, Hoogte: 219 mm



Kenmerken		Accu/Batterij	
UPS-topologie *	Line-interactive	Acculevensduur (max)	5 jaar
Output power capacity *	1,5 kVA	Accu/Batterij oplaadtijd	3 uur
Uitgangsvermogen *	1000 W	Hot-swap batterij	✓
Golfvorm *	Sinus	Automatische batterij test	✓
Ingang operation voltage (min) *	151 V	Koude start	✓
Ingang operation voltage (max) *	302 V		
Frequentie *	50/60 Hz		
Uitgang operation voltage (min)	220 V		
Uitgang operation voltage (max)	240 V		
Output frequentie	50/60 Hz		
Automatic Voltage Regulation (AVR)	✓		
Surge energy rating	459 J		
Output voltage THD	5 procent		
Geluidsniveau	45 dB		
Spanningsbeveiliging	✓		
Geluidsalarm(en)	✓		
Web-gebaseerd management	✓		
Hoorbare alarmstanden	Alarm bij werking op batterij, Alarm bij laag batterijniveau, Alarm bij overbelasting		
Auto-herstart	✓		
Temperatuurspanningscompensatie	✓		
Poorten & interfaces		Design	
Stopcontacttypes	C13 stekker, IEC Jumpers	Vormfactor *	Mini Tower
Stekker	C14 stekker	Snoerlengte	1,83 m
Aantal AC uitgangen	8 AC-uitgang(en)	Kleur van het product *	Zwart
USB-poort	✓	Type beeldscherm	LCD
Aantal USB 2.0-poorten	1	LED-indicatoren	✓
Seriële interface	✓	Certificering	CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE
Soort seriële aansluiting	RS-232		
Seriële poort(en)	1		
		Eisen aan de omgeving	
		Bedrijfstemperatuur (T-T)	0 - 40 °C
		Temperatuur bij opslag	-15 - 45 °C
		Relatieve vochtigheid in bedrijf (V-V)	0 - 95 procent
		Luchtvochtigheid bij opslag	0 - 95 procent
		Hoogte, in bedrijf	0 - 3000 m
		Hoogte bij opslag	0 - 15000 m
		Gewicht en omvang	
		Breedte	171 mm
		Diepte	439 mm
		Hoogte	219 mm
		Gewicht	24,1 kg
		Breedte verpakking	328 mm
		Diepte verpakking	595 mm
		Hoogte verpakking	376 mm
		Gewicht verpakking	27,2 kg

Poorten & interfaces		Verpakking	
Aantal Ethernet LAN (RJ-45)-poorten	1	Meegeleverde kabels	RS-232, USB-kabel
SmartSlot	✓	Snelle installatiehandleiding	✓
Accu/Batterij		Ondersteunings-cd	✓
Batterijtechnologie	Sealed Lead Acid (VRLA)	Software-cd	✓
Logistieke gegevens			
Producten per pallet		12 stuk(s)	
Code geharmoniseerd systeem (HS)		85078000	



0731304332992



731304332992

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 10-MAR-2023. Prints or copies of Information are only valid on the printed Publication date