



## APC Smart-UPS SMT2200RM12UC Noodstroomvoeding - 8x C13, 1x C19, USB, Rack Mountable, SmartConnect, 2200VA



**Merk :** APC

**Artikelcode:** SMT2200RM12UC

**Productnaam :** Smart-UPS SMT2200RM12UC  
Noodstroomvoeding - 8x C13, 1x C19, USB, Rack Mountable, SmartConnect, 2200VA


APC Smart-UPS SMT2200RM12UC Noodstroomvoeding - 8x C13, 1x C19, USB, Rack Mountable, SmartConnect, 2200VA

APC Smart-UPS SMT2200RM12UC Noodstroomvoeding - 8x C13, 1x C19, USB, Rack Mountable, SmartConnect, 2200VA. UPS-topologie: Line-interactive, Output power capacity: 2,2 kVA, Uitgangsvermogen: 1980 W. Aantal AC uitgangen: 9 AC-uitgang(en), USB-poorttype: USB Type-A, Soort serieële aansluiting: RJ-45. Batterijtechnologie: Sealed Lead Acid (VRLA), Acculevensduur (max): 5 jaar, Accu/Batterij oplaadtijd: 3 uur. Vormfactor: Rackmontage, Kleur van het product: Zwart, Metallic, Rackcapaciteit: 2U. Breedte: 480 mm, Diepte: 683 mm, Hoogte: 86 mm

Kenmerken		Accu/Batterij	
UPS-topologie *	Line-interactive	Accu/Batterij oplaadtijd	3 uur
Output power capacity *	2,2 kVA	Vervangings-batterij cartridge	RBC43
Uitgangsvermogen *	1980 W	<b>Design</b>	
Golfvorm *	Sinus	Vormfactor *	Rackmontage
Ingang operation voltage (min) *	151 V	Rackcapaciteit	2U
Ingang operation voltage (max) *	302 V	Snoerlengte	2 m
Frequentie *	50/60 Hz	Kleur van het product *	Zwart, Metallic
Uitgang operation voltage (min)	220 V	Type beeldscherm	LCD
Uitgang operation voltage (max)	240 V	Certificering	CE, EAC, EN 60950, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE
Surge energy rating	375 J	<b>Eisen aan de omgeving</b>	
Responstijd	6 ms	Bedrijfstemperatuur (T-T)	0 - 40 °C
Output voltage THD	5 procent	Temperatuur bij opslag	-15 - 45 °C
Geluidsniveau	55 dB	Relatieve vochtigheid in bedrijf (V-V)	0 - 95 procent
Stroomspanning bescherming	Overspanning	Luchtvochtigheid bij opslag	0 - 95 procent
Geluidsalarm(en)	✓	Hoogte, in bedrijf	0 - 3000 m
Hoorbare alarmstanden	Alarm bij werking op batterij, Alarm bij laag batterijniveau	Hoogte bij opslag	0 - 15000 m
<b>Poorten &amp; interfaces</b>		<b>Gewicht en omvang</b>	
Aantal AC uitgangen	9 AC-uitgang(en)	Breedte	480 mm
USB-poort	✓	Diepte	683 mm
Aantal USB 2.0-poorten	1	Hoogte	86 mm
USB-poorttype	USB Type-A	Gewicht	42,3 kg
Serieële interface	✓	Breedte verpakking	600 mm
Soort serieële aansluiting	RJ-45	Diepte verpakking	980 mm
Aantal Ethernet LAN (RJ-45)-poorten	1	Hoogte verpakking	254 mm
SmartSlot	✓	Gewicht verpakking	49,7 kg
<b>Accu/Batterij</b>		<b>Verpakking</b>	
Batterijtechnologie	Sealed Lead Acid (VRLA)	Rekbevestigingspakket	✓
Ondersteund aantal accu's/batterijen	1	Meegeleverde kabels	RS-232, USB-kabel
Acculevensduur (max)	5 jaar	Software-cd	✓
		<b>Logistieke gegevens</b>	
		Producten per pallet	8 stuk(s)
		Code geharmoniseerd systeem (HS)	85078000



0731304337324



731304337324

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.