



APC Smart-UPS SMT3000RMI2UC Noodstroomvoeding - 8x C13, 1x C19, USB, Rack Mountable, SmartConnect, 3000VA

Merk : APC

Artikelcode: SMT3000RMI2UC

Productnaam : Smart-UPS SMT3000RMI2UC
Noodstroomvoeding - 8x C13, 1x C19, USB, Rack Mountable, SmartConnect, 3000VA



APC Smart-UPS SMT3000RMI2UC Noodstroomvoeding - 8x C13, 1x C19, USB, Rack Mountable, SmartConnect, 3000VA

APC Smart-UPS SMT3000RMI2UC Noodstroomvoeding - 8x C13, 1x C19, USB, Rack Mountable, SmartConnect, 3000VA. UPS-topologie: Line-interactive, Output power capacity: 3 kVA, Uitgangsvermogen: 2700 W. Stopcontacttypes: C13 stekker, C19 stekker, Stekker: C20 stekker, Aantal AC uitgangen: 9 AC-uitgang(en). Batterijtechnologie: Sealed Lead Acid (VRLA), Batterij capaciteit: 547 VAh, Typische backup tijd op volledige lading: 3,2 min. Vormfactor: Rackmontage, Kleur van het product: Zwart, Rackcapaciteit: 2U. Breedte: 480 mm, Diepte: 683 mm, Hoogte: 86 mm



Kenmerken		Accu/Batterij	
UPS-topologie *	Line-interactive	Automatische batterij test	✓
Output power capacity *	3 kVA	Koude start	✓
Uitgangsvermogen *	2700 W	Design	
Golfvorm *	Sinus	Vormfactor *	Rackmontage
Ingang operation voltage (min) *	151 V	Rackcapaciteit	2U
Ingang operation voltage (max) *	302 V	Snoerlengte	2 m
Frequentie *	50/60 Hz	Kleur van het product *	Zwart
Uitgang operation voltage (min)	220 V	Type beeldscherm	LCD
Uitgang operation voltage (max)	240 V	LED-indicatoren	Status
Automatic Voltage Regulation (AVR)	✓	Certificering	CE, EAC, EN 60950, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE, REACH, PEP, EOL
Surge energy rating	320 J	Eisen aan de omgeving	
Contacttijd (min)	4 ms	Bedrijfstemperatuur (T-T)	0 - 40 °C
Contacttijd (max)	8 ms	Temperatuur bij opslag	-15 - 45 °C
Efficiëntie	98,9 procent	Relatieve vochtigheid in bedrijf (V-V)	0 - 95 procent
Geluidsniveau	55 dB	Luchtvochtigheid bij opslag	0 - 95 procent
Geluidsalarm(en)	✓	Hoogte, in bedrijf	0 - 3000 m
Auto-herstart	✓	Hoogte bij opslag	0 - 15000 m
Poorten & interfaces		Technische details	
Stopcontacttypes	C13 stekker, C19 stekker	Duurzaamheidscertificaten	RoHS
Stekker	C20 stekker	Gewicht en omvang	
Aantal AC uitgangen	9 AC-uitgang(en)	Breedte	480 mm
Number of output IEC jumpers	3	Diepte	683 mm
USB-poort	✓	Hoogte	86 mm
Seriële interface	✓	Gewicht	44,3 kg
Soort seriële aansluiting	RJ-45	Breedte verpakking	600 mm
Aantal Ethernet LAN (RJ-45)-poorten	1		
SmartSlot	✓		

Accu/Batterij		Gewicht en omvang	
Batterijtechnologie	Sealed Lead Acid (VRLA)	Diepte verpakking	980 mm
Batterij capaciteit	547 VAh	Hoogte verpakking	254 mm
Typische backup tijd op volledige lading	3,2 min	Gewicht verpakking	51,7 kg
Typische backup tijd op halve lading	11,5 min	Verpakking	
Acculevensduur (max)	5 jaar	Rekbevestigingspakket	✓
Accu/Batterij oplaadtijd	3 uur	Meegeleverde kabels	RS-232, USB-kabel
Hot-swap batterij	✓	Snelle installatiehandleiding	✓
		Software-cd	✓
		Meegeleverde software	Powershute Business Edition
		Logistieke gegevens	
		Code geharmoniseerd systeem (HS) 85078000	
		Overige specificaties	
		Netspanning, in bedrijf	230 V
		Nominale input voltage	230 V



0731304337348



731304337348



5706998907233

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.