

# DIGITUS 4K HDMI Extender Set, 70 m

DS-55519  
EAN 4016032482734



### HDMI Extender Set, 4K/30Hz 70 m, PoC, IR

The HDMI Extender Set extends Full HD AV signals over a distance of up to 70 m, 4K/30Hz signals can be extended over a distance of up to 40 m using a CAT6 (or higher) network cable. The transmitter unit features an HDMI loop out for connecting a local monitor. Thanks to PoC (Power over Cable), only the transmitter needs to be supplied with power. IR transmission makes it possible to conveniently control the signal source using remote control from the receiver (output screen). Other features include an EDID copy function of the output screen on the receiver or on the HDMI loop out, which can be selected using the changeover switch.

**Extends Full HD AV signals over a distance of up to 70 m, 4K/30Hz signals can be extended over a distance of up to 40 m using a CAT6 (or higher) network cable**

- Extends HDMI AV signals to a distance of up to 70 m
- Supports resolutions of up to 4K/30 Hz, 4:4:4
- Supports CAT 6, CAT 6A, CAT 7, CAT 8 network cable
- PoC (Power over Cable) - Only the transmitter requires an external power adapter
- HDMI loop-out / output - Connection of local monitor to the source device
- EDID copy function of the output screen on the receiver or on the HDMI loop out
- HDMI 1.4, HDCP 1.4, DVI 1.0
- IR transmission (unidirectional)
- Video bandwidth: 10.2 Gbps
- Transmitter unit connections:
- 1x HDMI input (4K/30Hz) - Connection signal source

- 1x HDMI loop-out / output - Connection of local monitor (source device)
- 1x RJ45 output - Connection CAT transmission cable
- 1x IR output - Connection of IR transmitter
- 1x Power adapter input (DC 12V/1A) - Connection for external power adapter
- 1x EDID changeover switch
- Receiver unit connections:
- 1x HDMI output (4K/30Hz) - Connection output device
- 1x RJ45 input - Connection CAT transmission cable
- 1 x IR input - Connection of IR receiver
- Suitable for wall mounting
- ESD protection
- Operating temperature: 0-40°
- Power consumption: Transmitter approx. approx. 1.86 W, receiver approx. 0.87 W
- Housing: Metal
- Dimensions (1 unit): L 7.9 x W 6.9 x H 1.65 cm
- Weight (1 unit): 130 g
- Weight (1 unit): 130 g
- Color: black
- KVM: no
- PoE (Power over Ethernet): yes

### Package contents

- 1x Transmitter unit
- 1x Receiver unit
- 1x IR transmission cable (1.5 m)
- 1x IR receiver cable (1.5 m)
- 1x Power adapter (DC 12V/1A, 1.15 m)
- 1x User manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	30	16.50	40.00	42.00	36.50	61,320.00
Packaging Unit Inside	1	0.55	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.55	11.30	20.00	7.50	1,695.00
Net single without Packaging	1	0.13	6.90	8.00	1.70	0.00

More images:

