



PORTABLE TYPE-C DOCKING

Contents

1.0 INTRODUCTION	2
2.0 FEATURES	2
3.0 SPECIFICATIONS	3
4.0 PACKAGE CONTENTS	4
5.0 CONNECTION DIAGRAM	4

DEAR CUSTOMER

Thank you for purchasing this product. For optimum performance and safety, please read these instructions carefully before connecting, operating or using this product. Please keep this manual for future reference.

1.0 INTRODUCTION

This is a portable multifunctional Type-C docking. It offers an integrated solution for data, video, power and Ethernet. It has one Type-C male(connect to Host PC), 2 Type-C female (one for data and another for PD charging), 2 USB-A female for data transmission, HDMI and VGA ports for enjoying high definition picture or video on big screen, SD/Micro SD slots and RJ45 port for Gigabit Ethernet. This docking is easy to carry, you can take it for business meeting or traveling anywhere you want.

2.0 FEATURES

- Interface:
 - Type-C Malex1 (connect to Type-C host PC)
 - Type-C Female x2 (one for data and one for PD Charging)
 - USB-A Female x2
 - HDMI Female x1
 - VGA female x1
 - RJ45 x1
 - SD slotx1, Micro SD slotx1
- Support HDMI resolution up to 4kx2k@30Hz
- Support VGA resolution up to 1920x1200@60Hz
- Allow one video port to work at one time (Priority: HDMI>VGA)
- Support 10/100 /1000Mbps for RJ45 port
- One USB-A (next to SD/Micro SD card slot) supports max 5V/1.5A downstream charging, another USB-A supports max 900mA downstream charging
- Both of the 2 USB-A ports support max 5Gbps data transmission
- Type-C data port supports max 5Gbps data transmission and max 1.5A downstream charging port
- 2 USB-A and Type-C data port share max 10W(5V/2A) downstream charging

- Support Secure Digital v3.0 UHS-I (Ultra High Speed): SDR12 (12.5Mbyte/s)/SDR25(25Mbyte/s)/SDR50(50Mbyte/s)/DDR50(50Mbyte/s)/SDR104(104Mbyte/s)
- Allow one card to work at one time when both SD and Micro SD card are connected
- Type-C charging port supports PD charging max 100W (20V/5A)
- Support Fast role swap of PD 3.0 the connected device will not get disconnected while plugging in and out PD Adapter when working on PD 3.0 device
- Reversible plug for Type-C ports
- Easy to Carry

3.0 SPECIFICATIONS

Input/Output Connector	
Input	Type-C Malex1 (connect to Type-C host PC)
Output	Type-C Female x2 (one for data and another for PD Charging) USB-A Female x2 HDMI Female x1 VGA Female x1 RJ45 x1 SD slotx1, Micro SD slotx1
Mechanical	
Size (L-W-H)	122*70*14mm
Weight (Net)	89.2g
Warranty	
Limited Warranty	1 Year
Resolutions	
HDMI	Max 4Kx2k@30Hz
VGA	Max 1920x1200@60Hz
Environmental	
Operating Temperature	0°C to +45°C
Operating Humidity	10% to 90 % RH (no condensation)
Storage Temperature	-10°C to +70°C
Storage Humidity	10% to 90 % RH (no condensation)

Power Supply	
Type-C PD Charging	Max 100W(20V/5A)
Regulatory Approvals	
Certifications	FCC,CE
Accessory Adapter	
User Manual	English Version

4.0 PACKAGE CONTENTS

Before attempting to use this unit, please check the packaging and make sure the following items are contained in the shipping carton:

- Main unit x1
- User Manual x1

5.0 CONNECTION DIAGRAM

