

Superior PCs

ESPRIMO



Windows®. Life without Walls™.

Fujitsu recommends Windows 7.

ESPRIMO P7935 E85+

Your expandable workhorse

Genuine Windows® 7 Professional
Genuine Windows Vista® Business (32-bit)
Genuine Windows Vista® Business (64-bit)
Genuine Windows Vista® Home Basic
Genuine Windows Vista® Home Premium
TwinLoad Windows® XP Professional (DVD)

Nero Essentials (burning software)

D2812-A2x (µBTX)

Intel® Q45

Intel® Celeron® 450, 512 KB, 800 MHz
Intel® Celeron® E1500, 512 KB, 800 MHz
Intel® Celeron® E3200, 1 MB, 800 MHz
Intel® Pentium® E5200, 2 MB, 800 MHz
Intel® Pentium® E5300, 2 MB, 800 MHz
Intel® Pentium® E5400, 2 MB, 800 MHz
Intel® Pentium® E6300, 2 MB, 1066 MHz
Intel® Core™2 Duo E7400, 3 MB, 1066 MHz
Intel® Core™2 Duo E7500, 3 MB, 1066 MHz
Intel® Core™2 Duo E7600, 3 MB, 1066 MHz
Intel® Core™2 Duo E8400, 6 MB, 1333 MHz
Intel® Core™2 Duo E8500, 6 MB, 1333 MHz
Intel® Core™2 Duo E8600, 6 MB, 1333 MHz
Intel® Core™2 Quad Q8300, 4 MB, 1333 MHz
Intel® Core™2 Quad Q9400, 6 MB, 1333 MHz
Intel® Core™2 Quad Q9505, 6 MB, 1333 MHz
Intel® Core™2 Quad Q9550, 12 MB, 1333 MHz
Intel® Core™2 Quad Q9650, 12 MB, 1333 MHz

up to 16 GB, 4 DIMM (DDR2) slot(s); 800 MHz
With future modules, dual channel support, for dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules)

4 x Serial ATA total

2 x optional

Serial ATA II, NCQ and 3 GBit, AHCI, Raid 1/0

1.44 MB Floppy, standard
DVD-ROM, SATA I
DVD Super Multi, SATA I
Blu-ray Disc Triple Writer, SATA I
MultiCard Reader 20in1; 3.5-inch, USB 2.0

SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 160 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical
SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T.
SSD SATA, 64 GB, 2.5-inch
SSD SATA, 128 GB, 2.5-inch

2 x 3.5-inch external bay
2 x 3.5-inch internal bay
2 x 5.25-inch external bay

1 x PCI-Express Gen2 x16
1 x PCI-Express x4 (mech. x8)
2 x PCI slots

Interfaces

1 x Audio: line-in / microphone
1 x Audio: line-in
1 x Audio: line-out
1 x Front audio: headphone
1 x Front audio: microphone
12 x USB 2.0 total
2 x USB front
6 x USB rear
4 x internal (thereof 2 optional rear)
1 x VGA
1 x DVI (optional)
1 x serial (9pin, 16 byte FIFO, 16550 compatible) (RS-232)
1 x parallel optional (25pin with EPP and ECP)
1 x Ethernet (RJ-45)
2 x Mouse / Keyboard (PS/2)

Graphics

Intel® GMA 4500 up to 256 MB

Graphic features

DirectX® 10

Audio codec

Realtek ALC663

LAN

10/100/1000 MBit/s Intel® 82567LM

Weight

Approx. 12 kg

Dimension (W x D x H)

203 x 390 x 392 mm

Power efficiency note

Power supply efficiency (at 230V; 20% / 50% / 100% load) : 85% / 87% / 85%

Special features

Intel® vPro™ technology, Green PC, up to 87 % energy efficient power supply, Blue Angel certified, Family Concept, Twinload

Superior PCs

ESPRIMO



Windows®. Life without Walls™.

Fujitsu recommends Windows 7.

ESPRIMO P7935 E-Star 5.0

Your expandable workhorse

Genuine Windows® 7 Professional
Genuine Windows Vista® Business (32-bit)
Genuine Windows Vista® Business (64-bit)
Genuine Windows Vista® Home Basic
Genuine Windows Vista® Home Premium
TwinLoad Windows® XP Professional (DVD)

Nero Essentials (burning software)

D2812-A2x (µBTX)

Intel® Q45

Intel® Celeron® E1500, 512 KB, 800 MHz
Intel® Celeron® E3200, 1 MB, 800 MHz
Intel® Pentium® E5200, 2 MB, 800 MHz
Intel® Pentium® E5300, 2 MB, 800 MHz
Intel® Pentium® E5400, 2 MB, 800 MHz
Intel® Pentium® E6300, 2 MB, 1066 MHz
Intel® Core™2 Duo E7400, 3 MB, 1066 MHz
Intel® Core™2 Duo E7500, 3 MB, 1066 MHz
Intel® Core™2 Duo E7600, 3 MB, 1066 MHz
Intel® Core™2 Duo E8400, 6 MB, 1333 MHz
Intel® Core™2 Duo E8500, 6 MB, 1333 MHz
Intel® Core™2 Duo E8600, 6 MB, 1333 MHz
Intel® Core™2 Quad Q8300, 4 MB, 1333 MHz
Intel® Core™2 Quad Q9400, 6 MB, 1333 MHz
Intel® Core™2 Quad Q9505, 6 MB, 1333 MHz
Intel® Core™2 Quad Q9550, 12 MB, 1333 MHz
Intel® Core™2 Quad Q9650, 12 MB, 1333 MHz

up to 16 GB, 4 DIMM (DDR2) slot(s); 800 MHz
With future modules, dual channel support, for dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules)

4 x Serial ATA total

2 x optional

Serial ATA II, NCQ and 3 GBit, AHCI, Raid 1/0

1.44 MB Floppy, standard
DVD-ROM, SATA I
DVD Super Multi, SATA I
Blu-ray Disc Triple Writer, SATA I
MultiCard Reader 20in1; 3.5-inch, USB 2.0

SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 160 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical
SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T.
SSD SATA, 64 GB, 2.5-inch
SSD SATA, 128 GB, 2.5-inch

2 x 3.5-inch external bay
2 x 3.5-inch internal bay
2 x 5.25-inch external bay

1 x PCI-Express Gen2 x16
1 x PCI-Express x4 (mech. x8)
2 x PCI slots

Interfaces

1 x Audio: line-in / microphone
1 x Audio: line-in
1 x Audio: line-out
1 x Front audio: headphone
1 x Front audio: microphone
12 x USB 2.0 total
2 x USB front
6 x USB rear
4 x internal (thereof 2 optional rear)
1 x VGA
1 x DVI (optional)
1 x serial (9pin, 16 byte FIFO, 16550 compatible) (RS-232)
1 x parallel optional (25pin with EPP and ECP)
1 x Ethernet (RJ-45)
2 x Mouse / Keyboard (PS/2)

Graphics

Intel® GMA 4500 up to 256 MB

Graphic features

DirectX® 10

Audio codec

Realtek ALC663

LAN

10/100/1000 MBit/s Intel® 82567LM

Weight

Approx. 12 kg

Dimension (W x D x H)

203 x 390 x 392 mm

Power efficiency note

Power supply efficiency (at 230V; 20% / 50% / 100% load) : 85% / 87% / 85%

Special features

Intel® vPro™ technology, Green PC, ENERGY STAR® 5.0, up to 87 % energy efficient power supply, Blue Angel certified, Family Concept, Twinload

Superior PCs

ESPRIMO



Windows®. Life without Walls™.

Fujitsu recommends Windows 7.

ESPRIMO P7935 0-Watt

The world's first 0-Watt PC

Genuine Windows® 7 Professional
Genuine Windows Vista® Business (32-bit)
Genuine Windows Vista® Business (64-bit)
Genuine Windows Vista® Home Basic
Genuine Windows Vista® Home Premium
TwinLoad Windows® XP Professional (DVD)

Nero Essentials (burning software)

D2812-A2x (µBTX)

Intel® Q45

Intel® Celeron® E1500, 512 KB, 800 MHz
Intel® Celeron® E3200, 1 MB, 800 MHz
Intel® Pentium® E5200, 2 MB, 800 MHz
Intel® Pentium® E5300, 2 MB, 800 MHz
Intel® Pentium® E5400, 2 MB, 800 MHz
Intel® Pentium® E6300, 2 MB, 1066 MHz
Intel® Core™2 Duo E7400, 3 MB, 1066 MHz
Intel® Core™2 Duo E7500, 3 MB, 1066 MHz
Intel® Core™2 Duo E7600, 3 MB, 1066 MHz
Intel® Core™2 Duo E8400, 6 MB, 1333 MHz
Intel® Core™2 Duo E8500, 6 MB, 1333 MHz
Intel® Core™2 Duo E8600, 6 MB, 1333 MHz
Intel® Core™2 Quad Q8300, 4 MB, 1333 MHz
Intel® Core™2 Quad Q9400, 6 MB, 1333 MHz
Intel® Core™2 Quad Q9505, 6 MB, 1333 MHz
Intel® Core™2 Quad Q9550, 12 MB, 1333 MHz
Intel® Core™2 Quad Q9650, 12 MB, 1333 MHz

up to 16 GB, 4 DIMM (DDR2) slot(s); 800 MHz
Dual channel support, for dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules)

4 x Serial ATA total

2 x optional

Serial ATA II, NCQ and 3 GBit, AHCI, Raid 1/0

1.44 MB Floppy, standard
DVD-ROM, SATA I
DVD Super Multi, SATA I
Blu-ray Disc Triple Writer, SATA I
MultiCard Reader 20in1; 3.5-inch, USB 2.0

SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 160 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical
SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T.
SSD SATA, 64 GB, 2.5-inch
SSD SATA, 128 GB, 2.5-inch

2 x 3.5-inch external bay
2 x 3.5-inch internal bay
2 x 5.25-inch external bay

1 x PCI-Express Gen2 x16
1 x PCI-Express x4 (mech. x8)
2 x PCI slots

Interfaces

1 x Audio: line-in / microphone
1 x Audio: line-in
1 x Audio: line-out
1 x Front audio: headphone
1 x Front audio: microphone
12 x USB 2.0 total
2 x USB front
6 x USB rear
4 x internal (thereof 2 optional rear)
1 x VGA
1 x DVI
1 x serial (9pi, 16 byte FIFO, 16550 compatible) (RS-232)
1 x parallel optional (25pin with EPP and ECP)
1 x Ethernet (RJ-45)
2 x Mouse / Keyboard (PS/2)

Graphics

Intel® GMA 4500 up to 256 MB

Graphic features

DirectX® 10

Audio codec

Realtek ALC663

LAN

10/100/1000 MBit/s Intel® 82567LM

Weight

Approx. 12 kg

Dimension (W x D x H)

203 x 390 x 392 mm

Power efficiency note

Power supply efficiency (at 230V; 20% / 50% / 100% load) : 86% / 89% / 87%

Special features

0-Watt in off- / hibernating mode, Intel® vPro™ technology, Green PC, ENERGY STAR® 5.0, 89 % energy efficient power supply, Blue Angel certified, Switched monitor outlet, Family Concept, Twinload

Advanced PCs

ESPRIMO



Windows®. Life without Walls™.

Fujitsu recommends Windows 7.

ESPRIMO P5730

Your expandable business workhorse

Genuine Windows® 7 Professional
Genuine Windows Vista® Business (32-bit)
Genuine Windows Vista® Business (64-bit)
Genuine Windows Vista® Home Basic
Genuine Windows Vista® Home Premium
TwinLoad Windows® XP Professional (DVD)

Nero Essentials (burning software)

D2811 (µBTX)

Intel® Q43

Intel® Celeron® 450, 512 KB, 800 MHz
Intel® Celeron® E1500, 512 KB, 800 MHz
Intel® Celeron® E3200, 1 MB, 800 MHz
Intel® Pentium® E5200, 2 MB, 800 MHz
Intel® Pentium® E5300, 2 MB, 800 MHz
Intel® Pentium® E5400, 2 MB, 800 MHz
Intel® Pentium® E6300, 2 MB, 1066 MHz
Intel® Core™2 Duo E7400, 3 MB, 1066 MHz
Intel® Core™2 Duo E7500, 3 MB, 1066 MHz
Intel® Core™2 Duo E7600, 3 MB, 1066 MHz
Intel® Core™2 Duo E8400, 6 MB, 1333 MHz
Intel® Core™2 Duo E8500, 6 MB, 1333 MHz
Intel® Core™2 Duo E8600, 6 MB, 1333 MHz
Intel® Core™2 Quad Q8300, 4 MB, 1333 MHz
Intel® Core™2 Quad Q9400, 6 MB, 1333 MHz
Intel® Core™2 Quad Q9505, 6 MB, 1333 MHz
Intel® Core™2 Quad Q9550, 12 MB, 1333 MHz
Intel® Core™2 Quad Q9650, 12 MB, 1333 MHz

Up to 16 GB, 4 DIMM (DDR2) slots; 800 MHz
With future modules, dual channel support, for dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules)

4 x Serial ATA total

2 x optional

Serial ATA II, NCQ and 3 GBit, AHCI

1.44 MB floppy, standard; MultiCard reader 15in1; 3.5-inch DVD-ROM; DVD Super Multi; Blu-ray Disc triple writer

SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 160 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T.
SSD SATA, 64 GB, 2.5-inch
SSD SATA, 128 GB, 2.5-inch

2 x 3.5-inch external bay
2 x 3.5-inch internal bay
2 x 5.25-inch external bay

1 x PCI-Express Gen2 x16
1 x PCI-Express x4 (mech. x8)
2 x PCI slots

Interfaces

1 x audio: line-in / microphone
1 x audio: line-in
1 x audio: line-out
1 x front audio: headphone
1 x front audio: microphone
1 x serial (9pi, 16 byte FIFO, 16550 compatible) (RS-232)
12 x USB 2.0 total
2 x USB front
6 x USB rear
4 x USB internal (thereof 2 optional rear)
1 x VGA
1 x DVI optional
1 x Ethernet RJ-45
2 x PS/2 (mouse/keyboard)

Graphics

Intel® GMA 4500 Up to 256 MB

Graphic features

DirectX® 10

Audio codec

Realtek ALC663

LAN

10/100/1000 MBit/s Intel® 82567LF

Weight

Approx. 12 kg

Dimension (W x D x H)

203 x 390 x 392 mm

Power efficiency note

Power supply efficiency (at 230V; 20%/50%/100% load): 71%/77%/76%

Special features

Green PC, Cabinet Lock, family concept, switched monitor outlet, Twinload

Advanced PCs

ESPRIMO



Windows®. Life without Walls™.

Fujitsu recommends Windows 7.

ESPRIMO P5730 E85+

The expandable business workhorse

Genuine Windows® 7 Professional
Genuine Windows Vista® Business (32-bit)
Genuine Windows Vista® Business (64-bit)
Genuine Windows Vista® Home Basic
Genuine Windows Vista® Home Premium
TwinLoad Windows® XP Professional (DVD)

Nero Essentials (burning software)

D2811 (µBTX)

Intel® Q43

Intel® Celeron® 450, 512 KB, 800 MHz
Intel® Celeron® E1500, 512 KB, 800 MHz
Intel® Celeron® E3200, 1 MB, 800 MHz
Intel® Pentium® E5200, 2 MB, 800 MHz
Intel® Pentium® E5300, 2 MB, 800 MHz
Intel® Pentium® E5400, 2 MB, 800 MHz
Intel® Pentium® E6300, 2 MB, 1066 MHz
Intel® Core™2 Duo E7400, 3 MB, 1066 MHz
Intel® Core™2 Duo E7500, 3 MB, 1066 MHz
Intel® Core™2 Duo E7600, 3 MB, 1066 MHz
Intel® Core™2 Duo E8400, 6 MB, 1333 MHz
Intel® Core™2 Duo E8500, 6 MB, 1333 MHz
Intel® Core™2 Duo E8600, 6 MB, 1333 MHz
Intel® Core™2 Quad Q8300, 4 MB, 1333 MHz
Intel® Core™2 Quad Q9400, 6 MB, 1333 MHz
Intel® Core™2 Quad Q9505, 6 MB, 1333 MHz
Intel® Core™2 Quad Q9550, 12 MB, 1333 MHz
Intel® Core™2 Quad Q9650, 12 MB, 1333 MHz

up to 16 GB, 4 DIMM (DDR2) slot(s); 800 MHz
With future modules, dual channel support, for dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules)

4 x Serial ATA total

2 x optional

Serial ATA II, NCQ and 3 GBit, AHCI

1.44 MB Floppy, standard
DVD-ROM, SATA I
DVD Super Multi, SATA I
Blu-ray Disc Triple Writer, SATA I
MultiCard Reader 20in1; 3.5-inch, USB 2.0

SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 160 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical
SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T.
SSD SATA, 64 GB, 2.5-inch
SSD SATA, 128 GB, 2.5-inch

2 x 3.5-inch external bay
2 x 3.5-inch internal bay
2 x 5.25-inch external bay

1 x PCI-Express Gen2 x16
1 x PCI-Express x4 (mech. x8)
2 x PCI slots

Interfaces

1 x Audio: line-in / microphone
1 x Audio: line-in
1 x Audio: line-out
1 x Front audio: headphone
1 x Front audio: microphone
12 x USB 2.0 total
2 x USB front
6 x USB rear
4 x internal (thereof 2 optional rear)
1 x VGA
1 x DVI (optional)
1 x serial (9pin, 16 byte FIFO, 16550 compatible) (RS-232)
1 x parallel optional (25pin with EPP and ECP)
1 x Ethernet (RJ-45)
2 x Mouse / Keyboard (PS/2)

Graphics

Intel® GMA 4500 up to 256 MB

Graphic features

DirectX® 10

Audio codec

Realtek ALC663

LAN

10/100/1000 MBit/s Intel® 82567LF

Weight

Approx. 12 kg

Dimension (W x D x H)

203 x 390 x 392 mm

Power efficiency note

Power supply efficiency (at 230V; 20% / 50% / 100% load) : 85% / 87% / 85%

Special features

Green PC, up to 87 % energy efficient power supply, Blue Angel certified, Family Concept, Twinload, Service-friendly cabinet with EasyChange, EasyFix, EasyPull, FlexySlot

Advanced PCs

ESPRIMO



Windows®. Life without Walls™.

Fujitsu recommends Windows 7.

ESPRIMO P5730 E-Star 5.0

The expandable business workhorse

Genuine Windows® 7 Professional
Genuine Windows Vista® Business (32-bit)
Genuine Windows Vista® Business (64-bit)
Genuine Windows Vista® Home Basic
Genuine Windows Vista® Home Premium
TwinLoad Windows® XP Professional (DVD)

Nero Essentials (burning software)

D2811 (µBTX)

Intel® Q43

Intel® Celeron® E1500, 512 KB, 800 MHz
Intel® Celeron® E3200, 1 MB, 800 MHz
Intel® Pentium® E5200, 2 MB, 800 MHz
Intel® Pentium® E5300, 2 MB, 800 MHz
Intel® Pentium® E5400, 2 MB, 800 MHz
Intel® Pentium® E6300, 2 MB, 1066 MHz
Intel® Core™2 Duo E7400, 3 MB, 1066 MHz
Intel® Core™2 Duo E7500, 3 MB, 1066 MHz
Intel® Core™2 Duo E7600, 3 MB, 1066 MHz
Intel® Core™2 Duo E8400, 6 MB, 1333 MHz
Intel® Core™2 Duo E8500, 6 MB, 1333 MHz
Intel® Core™2 Duo E8600, 6 MB, 1333 MHz
Intel® Core™2 Quad Q8300, 4 MB, 1333 MHz
Intel® Core™2 Quad Q9400, 6 MB, 1333 MHz
Intel® Core™2 Quad Q9505, 6 MB, 1333 MHz
Intel® Core™2 Quad Q9550, 12 MB, 1333 MHz
Intel® Core™2 Quad Q9650, 12 MB, 1333 MHz

up to 16 GB, 4 DIMM (DDR2) slot(s); 800 MHz
With future modules, dual channel support, for dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules)

4 x Serial ATA total

2 x optional

Serial ATA II, NCQ and 3 GBit, AHCI

1.44 MB Floppy, standard
DVD-ROM, SATA I
DVD Super Multi, SATA I
Blu-ray Disc Triple Writer, SATA I
MultiCard Reader 20in1; 3.5-inch, USB 2.0

SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 160 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical
SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T.
SSD SATA, 64 GB, 2.5-inch
SSD SATA, 128 GB, 2.5-inch

2 x 3.5-inch external bay
2 x 3.5-inch internal bay
2 x 5.25-inch external bay

1 x PCI-Express Gen2 x16
1 x PCI-Express x4 (mech. x8)
2 x PCI slots

Interfaces

1 x Audio: line-in / microphone
1 x Audio: line-in
1 x Audio: line-out
1 x Front audio: headphone
1 x Front audio: microphone
12 x USB 2.0 total
2 x USB front
6 x USB rear
4 x internal (thereof 2 optional rear)
1 x VGA
1 x DVI (optional)
1 x serial (9pin, 16 byte FIFO, 16550 compatible) (RS-232)
1 x parallel optional (25pin with EPP and ECP)
1 x Ethernet (RJ-45)
2 x Mouse / Keyboard (PS/2)

Graphics

Intel® GMA 4500 up to 256 MB

Graphic features

DirectX® 10

Audio codec

Realtek ALC663

LAN

10/100/1000 MBit/s Intel® 82567LF

Weight

Approx. 12 kg

Dimension (W x D x H)

203 x 390 x 392 mm

Power efficiency note

Power supply efficiency (at 230V; 20% / 50% / 100% load) : 85% / 87% / 85%

Special features

Green PC, ENERGY STAR® 5.0, up to 87 % energy efficient power supply, Blue Angel certified, Family Concept, Twinload, Service-friendly cabinet with EasyChange, EasyFix, EasyPull, FlexySlot

Advanced PCs

ESPRIMO



Windows®. Life without Walls™.

Fujitsu recommends Windows 7.

ESPRIMO P5635 E85+

Your expandable workhorse

Genuine Windows® 7 Professional
Genuine Windows Vista® Business (32-bit)
Genuine Windows Vista® Business (64-bit)
Genuine Windows Vista® Home Basic
Genuine Windows Vista® Home Premium
TwinLoad Windows® XP Professional (DVD)

Nero Essentials (burning software)

D2901 (µBTX)

NVIDIA® MCP78PV

AMD Sempron™ LE-1300, 512 KB, 1600 MHz
AMD Athlon™ LE-1660, 512 KB, 2000 MHz
AMD Athlon™ X2 5000B, 2 x 512 KB, 2000 MHz
AMD Athlon™ II X2 240e, 2 MB, 3600 MHz
AMD Athlon™ X2 5600B, 2 x 512 KB, 2000 MHz
AMD Athlon™ II X2 240, 2 MB, 3600 MHz
AMD Phenom™ II X2 545, 7 MB, 3600 MHz
AMD Phenom™ II X3 710, 7.5 MB, 3600 MHz
AMD Phenom™ II X4 925, 8 MB, 3600 MHz
AMD Phenom™ II X4 945, 8 MB, 3600 MHz

up to 16 GB, 4 DIMM (DDR2) slot(s); 800 MHz
Dual channel support, for dual channel performance,
a minimum of 2 memory modules have to be ordered,
capacity per channel has to be the same

4 x Serial ATA total

1 x optional

Serial ATA II, 3 GBit, Raid 1/0

1.44 MB Floppy, standard
DVD-ROM, SATA I
DVD Super Multi, SATA I
Blu-ray Disc Triple Writer, SATA I
MultiCard Reader 20in1; 3.5-inch, USB 2.0

SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 160 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical
SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T.
SSD SATA, 64 GB, 2.5-inch
SSD SATA, 128 GB, 2.5-inch

2 x 3.5-inch external bay
2 x 3.5-inch internal bay
2 x 5.25-inch external bay

1 x PCI-Express Gen2 x1
1 x PCI-Express x16
2 x PCI slots

Interfaces

1 x Audio: line-in / microphone
1 x Audio: line-in
1 x Audio: line-out
1 x Front audio: headphone
1 x Front audio: microphone
10 x USB 2.0 total
2 x USB front
6 x USB rear
2 x internal (thereof 2 optional rear)
1 x VGA
1 x DVI (optional)
1 x serial (9pi, 16 byte FIFO, 16550 compatible) (RS-232)
1 x parallel optional (25pin with EPP and ECP)
1 x Ethernet (RJ-45), 2 x Mouse / Keyboard (PS/2)

Graphics

NVIDIA® GeForce® 9200 up to 256 MB

Graphic features

DirectX® 10

Audio codec

Realtek ALC262

LAN

10/100/1000 MBit/s Broadcom BCM5787

Weight

Approx. 12 kg

Dimension (W x D x H)

203 x 390 x 392 mm

Power efficiency note

Power supply efficiency (at 230V; 20% / 50% / 100% load) : 85% / 87% / 85%

Special features

Green PC, up to 87 % energy efficient power supply, Blue Angel certified,
Family Concept, Cabinet lock, Keyboard power on, Service-friendly cabinet
with EasyChange, EasyFix and Easy Pull

Advanced PCs

ESPRIMO



Windows®. Life without Walls™.
Fujitsu recommends Windows 7.

ESPRIMO P5635 E-Star 5.0

Your expandable workhorse

Genuine Windows® 7 Professional
 Genuine Windows Vista® Business (32-bit)
 Genuine Windows Vista® Business (64-bit)
 Genuine Windows Vista® Home Basic
 Genuine Windows Vista® Home Premium
 TwinLoad Windows® XP Professional (DVD)

Nero Essentials (burning software)

D2901 (µBTX)

NVIDIA® MCP78PV

AMD Sempron™ LE-1300, 512 KB, 1600 MHz
 AMD Athlon™ LE-1660, 512 KB, 2000 MHz
 AMD Athlon™ X2 5000B, 2 x 512 KB, 2000 MHz
 AMD Athlon™ II X2 240e, 2 MB, 3600 MHz
 AMD Athlon™ X2 5600B, 2 x 512 KB, 2000 MHz
 AMD Athlon™ II X2 240, 2 MB, 3600 MHz
 AMD Phenom™ II X2 545, 7 MB, 3600 MHz
 AMD Phenom™ II X3 710, 7.5 MB, 3600 MHz
 AMD Phenom™ II X4 925, 8 MB, 3600 MHz
 AMD Phenom™ II X4 945, 8 MB, 3600 MHz

up to 16 GB, 4 DIMM (DDR2) slot(s); 800 MHz
 Dual channel support, for dual channel performance,
 a minimum of 2 memory modules have to be ordered,
 capacity per channel has to be the same

4 x Serial ATA total

1 x optional

Serial ATA II, 3 GBit, Raid 1/0

1.44 MB Floppy, standard
 DVD-ROM, SATA I
 DVD Super Multi, SATA I
 Blu-ray Disc Triple Writer, SATA I
 MultiCard Reader 20in1; 3.5-inch, USB 2.0

SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T.
 SATA II, 7200 rpm, 160 GB, 3.5-inch, S.M.A.R.T.
 SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T.
 SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical
 SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T.
 SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T.
 SSD SATA, 64 GB, 2.5-inch
 SSD SATA, 128 GB, 2.5-inch

2 x 3.5-inch external bay
 2 x 3.5-inch internal bay
 2 x 5.25-inch external bay

1 x PCI-Express x1
 1 x PCI-Express Gen2 x16
 2 x PCI slots

Interfaces

1 x Audio: line-in / microphone
 1 x Audio: line-in
 1 x Audio: line-out
 1 x Front audio: headphone
 1 x Front audio: microphone
 10 x USB 2.0 total
 2 x USB front
 6 x USB rear
 2 x internal (thereof 2 optional rear)
 1 x VGA
 1 x DVI
 1 x serial (9pi, 16 byte FIFO, 16550 compatible) (RS-232)
 1 x parallel optional (25pin with EPP and ECP)
 1 x Ethernet (RJ-45)
 2 x Mouse / Keyboard (PS/2)

Graphics

NVIDIA® GeForce® 9200 up to 256 MB

Graphic features

DirectX® 10

Audio codec

Realtek ALC262

LAN

10/100/1000 MBit/s Broadcom BCM5787

Weight

Approx. 12 kg

Dimension (W x D x H)

203 x 390 x 392 mm

Power efficiency note

Power supply efficiency (at 230V; 20% / 50% / 100% load) : 85% / 87% / 85%

Special features

Green PC, ENERGY STAR® 5.0, up to 87 % energy efficient power supply,
 Blue Angel certified, Family Concept, Cabinet lock, Keyboard power on,
 Service-friendly cabinet with EasyChange, EasyFix and Easy Pull

All-round PCs

ESPRIMO



ESPRIMO P1500

The wide-ranging home office and multimedia PC

Genuine Windows® 7 Home Premium
Genuine Windows Vista® Home Premium

D2950 (reduced µATX)

NVIDIA® MCP73PV

Intel® Pentium® E5300, 2 MB, 800 MHz
Intel® Core™2 Duo E7400, 3 MB, 1066 MHz
Intel® Core™2 Quad Q8300, 4 MB, 1333 MHz

NVIDIA® GeForce® G210, 512 MB
NVIDIA® GeForce® GT 220, 1 GB

up to 4 GB, 2 DIMM (DDR2) slot(s); 800 MHz
For combinations of 32 bit operating systems with 4 GB of memory or above the accessible memory may be reduced to 3.5 GB or less (depending on system configuration).

4 x Serial ATA total

Serial ATA II, 3 GBit

DVD Super Multi, SATA I
Blu-ray combo drive, SATA I

SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T.
SATA II, 7200 rpm, 1500 GB, 3.5-inch, S.M.A.R.T.

1 x 3.5-inch external bay
2 x 3.5-inch internal bay
2 x 5.25-inch external bay

1 x PCI-Express x1
1 x PCI-Express x16
2 x PCI slots

1 x Audio: line-in / microphone
1 x Audio: line-in
1 x Audio: line-out
1 x Front audio: headphone
1 x Front audio: microphone
1 x serial (9pi, 16 byte FIFO, 16550 compatible) (RS-232)
8 x USB 2.0 total
2 x USB front
4 x USB rear
2 x USB internal
1 x VGA
1 x Ethernet (RJ-45)
1 x HDMI
2 x Mouse / Keyboard (PS/2)

DirectX® 9

Realtek ALC663

10/100/1000 MBit/s

175 x 425 x 353 mm

Attractive price, made in Europe

Windows®. Life without Walls™.

Fujitsu recommends Windows 7.



ESPRIMO Q1500

The small, energy-efficient entertainer for living-room and office

Genuine Windows® 7 Home Premium
Genuine Windows Vista® Home Premium

Nero 8 Essentials S

Intel® GM45

Intel® Celeron® 900, 1 MB, 800 MHz
Intel® Core™2 Duo T6670, 2 MB, 800 MHz
Intel® Core™2 Duo P8700, 3 MB, 1066 MHz

up to 4 GB, 2 SODIMM slot(s); 800 MHz
Dual channel support, for dual channel performance, a minimum of 2 memory modules have to be ordered, capacity per channel has to be the same;
In configurations with 4 GB the visible memory may be reduced to approximately 3.5 GB or less (for 32 bit operating systems, depending on system configuration).

3 x Serial ATA total

1 x external on rear side

Serial ATA II, 3 GBit, AHCI

DVD Super Multi Slot-in slim, SATA
Blu-ray Combo SATA Slot-in slim, SATA

SATA, 5400 rpm, 160 GB, 2.5-inch
SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T.
SATA, 5400 rpm, 250 GB, 2.5-inch
SSD SATA, 64 GB, 2.5-inch
SSD SATA, 128 GB, 2.5-inch

1 x 2.5-inch bay
1 x 5.25-inch external bay

1 x Audio: line-in / microphone
1 x Audio: line-in
1 x Audio: line-out / headphones / SPDIF (optical)
6 x USB 2.0 total
2 x USB front
4 x USB rear
1 x Ethernet (RJ-45)
1 x DVI
1 x VGA via DVI to VGA-Adapter
1 x HDMI via DVI to HDMI-Adapter

Mobile Intel® GMA 4500M HD

DirectX® 10 (Windows Vista® Business),
DualView possible with DVI and VGA, HDCP support

Realtek ALC888

10/100/1000 MBit/s Intel® 82567LF (optional)

Approx. 1.7 kg

165 x 165 x 50 mm

Bluetooth 2.0

Bluetooth
WLAN

Mobile on desktop, extremely space-saving design, remote control optional, most energy-efficient computing