


# CS1732B / CS1734B

## 2/4-Port USB 2.0 KVM™ Switch with OSD

The CS1732B / CS1734B are 2/4-port KVM switches combined with a 2-port USB 2.0 hub. As KVM switches, they allow users to access two or four computers from a single keyboard, monitor, and mouse console. There are three methods to obtain instant access to any computer in your installation: Manual, Hotkey, and OSD.



### Setup



### Features

- 2/4-port KVM switch with USB 2.0 support and 2.1 surround sound audio
- One console controls two (CS1732B) or four (CS1734B) computers and two additional USB devices
- 2-port USB 2.0 hub built in
- USB 2.0 compliant
- Dual interface – supports computers with PS/2 or USB keyboard and mouse configurations
- Audio enabled – full bass response provides a rich experience for 2.1 surround sound systems
- Console audio ports on front panel for easy access – ideal for IP phone users
- Supports both USB and PS/2 keyboards and mice – configurations available with the included USB-to-PS/2 converter: USB keyboard and mouse; PS/2 keyboard and mouse; or PS/2 keyboard and USB mouse
- Independent switching of KVM, USB, and audio focus
- Superior video quality; 2048 x 1536; DDC2B
- Supports widescreen resolutions
- Computer selection via front panel pushbuttons, OSD (On Screen Display), and hotkeys
- Multiplatform support: Windows 2000/XP/Vista, Linux, Mac, and Sun
- Console mouse port emulation / bypass feature supports full mouse driver and multifunction mice
- Display Emulation Technology – the KVM switch reads and remembers the monitor's brand and display information
- Complete keyboard emulation for error-free booting
- Sun/Mac keyboard support and emulation\*
- Auto Scan Mode for monitoring all computers
- LED Display For Easy Status Monitoring
- Easy installation – no software required
- Firmware upgradeable

\*1. PC keyboard combinations emulate Sun/Mac keyboards  
2. Sun/Mac keyboards only work with their own computers

### Specifications

Function		CS1732B	CS1734B	
Computer Connections		2	4	
Port Selection		OSD; Hotkey; Pushbutton		
Connectors	Console Ports	Keyboard	1 x USB Type A Female (Black)	
		Video	1 x HDB-15 Female (Blue)	
		Mouse	1 x USB Type A Female (Black)	
		Speaker	2 x Mini Stereo Jack Female (Green)	
		Mic.	2 x Mini Stereo Jack Female (Pink)	
	KVM Ports	Keyboard	2 x SPHD-15 Female (Yellow)	4 x SPHD-15 Female (Yellow)
		Video	2 x Mini Stereo Jack Female (Green)	4 x Mini Stereo Jack Female (Green)
		Mouse	2 x Mini Stereo Jack Female (Pink)	4 x Mini Stereo Jack Female (Pink)
		Speaker	2 x Mini Stereo Jack Female (Green)	4 x Mini Stereo Jack Female (Green)
		Mic.	2 x Mini Stereo Jack Female (Pink)	4 x Mini Stereo Jack Female (Pink)
F/W Upgrade		1 x 4-conductor 3.5mm Jack (Black)		
Power		1 x DC Jack		
USB Hub		2 x USB Type A Female (White)		
Switches	Selected	2 x Pushbutton	4 x Pushbutton	
LEDs	On Line / Selected	2 (Orange)	4 (Orange)	
	USB Link	2 (Green)	4 (Green)	
Emulation		Keyboard / Mouse: PS/2; USB		
Video		2048 x 1536 @ 60Hz; DDC2B		
Scan Interval		1-99 seconds (Default: 5 sec.)		
Power Consumption		DC5.3V, 3.1W	DC5.3V, 3.4W	
Environment	Operating Temp.	0-50°C		
	Storage Temp.	-20-60°C		
	Humidity	0-80% RH, Non- condensing		
Physical Properties	Housing	Metal		
	Weight	0.55 kg	0.78 kg	
Dimensions (L x W x H)		13.98 x 8.70 x 5.55 cm	20.98 x 8.80 x 5.55 cm	

\* The specifications and pictures are subject to change without notice.