

4 Port USB 3.0 Hub plus 3 Dedicated USB Charging Ports (2 x 1A & 1 x 2A) - Wall Mountable Metal Enclosure

StarTech ID: ST4300U3C3



The ST4300U3C3 USB 3.0 Hub enables simultaneous data hub and USB charging functionality by adding three dedicated USB charge ports, as well as four USB 3.0 data ports, for a total of seven ports, all through a single USB 3.0 host connection.

The USB hub ports are compliant with the SuperSpeed USB 3.0 specification, offering data transfer rates up to 5 Gbps, and are backward compatible with USB 2.0 and 1.x specifications.

This externally powered USB hub also integrates 3 dedicated USB charging ports, providing 2 x 1A and 1 x 2A ports, enabling both data hub and USB charging station functionality. Support for USB Battery Charging Specification 1.2 lets you charge most mobile devices, including the Apple® iPhone®, iPad®, Microsoft® Surface™, Samsung Galaxy Tab™ and more.

Designed for easy access to the ports when connecting or disconnecting devices, the hub features an upright port orientation, in a compact and durable metal enclosure. For added flexibility, the hub includes a bracket for wall-mounted installations.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Användning

- Use in IT helpdesk or tech bench environments to provide USB hub and charge ports for multiple devices
- Installation in locations where USB 3.0 ports need to be securely mounted to a surface, such as a wall or under a desk
- Expand your USB 3.0 capabilities at home or in the office

Funktioner

- Provides 4 USB 3.0 hub ports, and 3 dedicated USB charging ports (2 x 1A, 1 x 2A)
- Supports USB Battery Charging Specification 1.2, including Apple® and Samsung Galaxy™ devices
- Compliant with SuperSpeed USB 3.0, with support for up to 5 Gbps
- Backward compatible with USB 2.0 and 1.x devices
- Compact, metal enclosure
- Includes wall-mount bracket

Tekniska specifikationer

Warranty	2 Years
Bus Type	USB 3.0
Industry Standards	USB Battery Charging Specification Rev. 1.2
Ports	7
Connector Type(s)	1 - USB 3.0 B (9 pin; SuperSpeed) Female
Connector Type(s)	3 - USB A (4 pin) Female
Connector Type(s)	4 - USB 3.0 A (9 pin; SuperSpeed) Female
Maximum Data Transfer Rate	5 Gbps
Type and Rate	USB 3.0 - 5 Gbit/s
OS Compatibility	Windows® 8 (32/64), 7 (32/64), Vista (32/64), XP (32/64) Windows® Server 2012, 2008 R2, 2003 (32/64) Mac OS 10.5 and up (Tested up to 10.9) Linux kernel 2.4 and above
System and Cable Requirements	Available USB 3.0 Port
Color	Svart
Enclosure Type	Aluminum
Product Height	24 mm [0.9 in]
Product Length	110 mm [4.3 in]
Product Weight	131 g [4.6 oz]
Product Width	45 mm [1.8 in]
LED Indicators	1 - Power
LED Indicators	4 - Hub Port Connection LEDs
Center Tip Polarity	Positive
Input Current	1.3 A
Input Voltage	100 ~ 240 AC
Output Current	3 A
Output Voltage	12 DC
Plug Type	M
Humidity	20~80% RH
Operating Temperature	5°C to 35°C (41°F to 95°F)
Storage Temperature	-20°C to 50°C (-4°F to 122°F)
Shipping (Package) Weight	558 g [19.7 oz]
Included in Package	1 - USB Charging Hub
Included in Package	1 - USB 3.0 Cable
Included in Package	1 - Wall Mount Bracket (w/ Screws)
Included in Package	4 - Rubber Feet
Included in Package	1 - Universal Power Adapter (NA/UK/EU)
Included in Package	1 - Instruction Manual

Certifikat, rapporter och kompatibilitet

