

SuperServer 5018D-MTF



Integrated Board



Super X10SLM-F

Available Colors:

Black



Key Features

1. Single socket H3 (LGA 1150) supports Intel® Xeon® E3-1200 v3/v4, 4th gen. Core i3, Pentium, Celeron processors
2. Intel® C224 Express PCH
3. 4x 3.5" Hot-swap SATA3 HDD bays
4. 1x PCI-E 3.0 x8 (in x16) Full-height slot
5. Up to 32GB DDR3 ECC 1600MHz UDIMMs in 4 sockets
6. Dual Gigabit Ethernet LAN ports (1x Intel® i217LM & 1x Intel® i210AT)
7. IPMI 2.0 on Dedicated LAN port
8. 350W Gold Level Power Supply

Note: Image above may show a varied configuration or optional parts, Please refer to parts list for standard parts included.

Specifications

Product SKUs

SYS-5018D-MTF ■ SuperServer 5018D-MTF (Black)

Motherboard

Super X10SLM-F

Processor/Cache

CPU ■ Intel® Xeon® processor E3-1200 v3/v4 family, 4th Gen Core i3, Pentium, Celeron processors
 ■ Socket H3 (LGA 1150)

System Memory

Memory Capacity ■ 4x 240-pin DDR3 DIMM slots
 ■ Supports up to 32 GB DDR3 ECC Un-Buffered memory (UDIMM)

Memory Type ■ 1600MHz ECC DDR3 SDRAM 72-bit, 240-pin gold-plated DIMMs

DIMM Sizes ■ 8GB, 4GB, 2GB, 1GB

Memory Voltage ■ 1.5 V

Error Detection ■ Corrects single-bit errors
 ■ Detects double-bit errors (using ECC memory)

Chassis

Form Factor ■ 1U Rackmount

Model ■ CSE-813MTQ-350CB

Dimensions and Weight

Height ■ 1.7" (43mm)

Width ■ 17.2" (437mm)

Depth ■ 19.8" (503mm)

Weight ■ Gross Weight: 30.4 lbs (13.8 kg)
 ■ Net Weight: 17.6 lbs (8 kg)

Available Colors ■ Black

Front Panel

Buttons ■ Power On/Off button
 ■ System Reset button


LEDs ■ Power LED
 ■ Hard drive activity LED
 ■ 2x Network activity LEDs
 ■ System Overheat LED

Ports ■ 2x USB ports
 ■ 1x Serial COM Port

Expansion Slots

PCI-Express ■ 1x PCI-E 3.0 x8 (in x16) Full-height slot*

On-Board Devices	
Chipset	<ul style="list-style-type: none"> Intel® C224 Express PCH
SATA	<ul style="list-style-type: none"> SATA3 (6Gbps) w/ RAID 0, 1, 10, 5 SATA2 (3Gbps) w/ RAID 0, 1
IPMI	<ul style="list-style-type: none"> Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support ASPEED AST2400 BMC with 10/100/1000Mbps
Network Controllers	<ul style="list-style-type: none"> Intel® i217LM + Intel® i210AT Controllers Supports 10BASE-T, 100BASE-TX, and 1000BASE-T, RJ45 output 1x Realtek RTL8201N PHY (dedicated IPMI)
VGA	<ul style="list-style-type: none"> ASPEED AST2400 BMC
Input / Output	
Serial ATA	<ul style="list-style-type: none"> 4x SATA3 (6Gbps) ports 2x SATA2 (3Gbps) ports SATA DOM Power Connector
LAN	<ul style="list-style-type: none"> 2x RJ45 LAN ports 1x RJ45 Dedicated IPMI LAN port
USB	<ul style="list-style-type: none"> 4x USB 3.0 ports (1 Type-A, 2+1 via header) 6x USB 2.0 ports (4 rear, 2 via header)
VGA	<ul style="list-style-type: none"> 1x VGA port
Serial Port / Header	<ul style="list-style-type: none"> 1x Fast UART 16550 serial port 1x internal header
PC Health Monitoring	
Voltage	<ul style="list-style-type: none"> Monitors for CPU Cores, +12V, +3.3V, +5V, +5V Standby, VBAT, HT, Memory, Chipset Voltages. 5-Phase-switching voltage regulator with auto-sense from 0.8375V-1.60V
FAN	<ul style="list-style-type: none"> Total of five 4-pin fan headers supporting up to 5 fans 5x fans with tachometer status monitoring Status monitor for speed control Status monitor for on/off control Support 3-pin fans (w/o speed control) Low noise fan speed control Pulse Width Modulated (PWM) fan connectors
Temperature	<ul style="list-style-type: none"> Monitoring for CPU and chassis environment CPU thermal trip support FC temperature sensing logic Thermal Monitor 2 (TM2) support PECI
LED	<ul style="list-style-type: none"> CPU / System Overheat LED +5V Standby alert LED
Other Features	<ul style="list-style-type: none"> Chassis intrusion detection Chassis intrusion header

Drive Bays	
Hot-swap	<ul style="list-style-type: none"> 4x 3.5" Hot-swap SATA3 HDDs w/ RAID
Peripheral Bay	<ul style="list-style-type: none"> Slim optical drive (optional)
Backplane	
SAS2/SATA3 HDD Backplane (SAS support requires optional SAS controller)	
System Cooling	
Fans	<ul style="list-style-type: none"> 4x 4cm 12,500 RPM PWM fans Optional fans to cool add-on cards
Power Supply	
350W AC power supply w/ PFC	
AC Voltage	<ul style="list-style-type: none"> 100-240 V, 50-60 Hz, 4.2-1.8 Amp
+5V	<ul style="list-style-type: none"> 18 Amp
+5V standby	<ul style="list-style-type: none"> 3 Amp
+12V	<ul style="list-style-type: none"> 29 Amp
+3.3V	<ul style="list-style-type: none"> 15 Amp
Certification	 <p>Gold Certified [Test Report]</p>
System BIOS	
BIOS Type	<ul style="list-style-type: none"> 128Mb SPI Flash EEPROM with AMI BIOS
BIOS Features	<ul style="list-style-type: none"> DMI 2.3 PCI 2.3 ACPI 1.0 / 2.0 USB Keyboard support SMBIOS 2.3
Management	
Software	<ul style="list-style-type: none"> IPMI (Intelligent Platform Management Interface) v2.0 with KVM support SuperDoctor® III Watch Dog NMI
Power Configurations	<ul style="list-style-type: none"> ACPI / ACPM Power Management Main Switch Override Mechanism Power-on mode for AC power recovery Internal/External modem ring-on
Operating Environment / Compliance	
RoHS	<ul style="list-style-type: none"> RoHS2 (2011/65/EU) Compliant
Environmental Spec.	<ul style="list-style-type: none"> Operating Temperature: 10°C to 35°C (50°F to 95°F) Non-operating Temperature: -40°C to 70°C (-40°F to 158°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)

Parts List

Parts List - (Items Included)

	Part Number	Qty	Description
Motherboard / Chassis	MBD-X10SLM-F	1	Super X10SLM-F Motherboard
	CSE-813MTQ-350CB	1	1U Chassis
Air Shroud	MCP-310-19007-0N	1	SC811/SC512L/SC512F/SC813M/SC113M/SC513L-410B/SC513L-420B/SC513F, UP X9SRE/I, X9 Mylar Air Shroud, 12"x9.6" MB
Backplane	BPN-SAS-815TQ	1	Sup 4x SAS/SATA;SATA con
Cable 1	CBL-0157L	1	8 pin to 8 pin ribbon SGPIO cable with tube , 40cm, PBF
Cable 2	CBL-0186L	1	SET OF 4 SATA 56/45.5/35/23CM ROUND S-RA. 26AWG
Manual	MNL-1459-QRG	1	5018D-MTF/MTRF, QRG
Riser Card	RSC-RR1U-E16	1	RSC-RR1U-E16 with PCI-E x16 output
Heatsink / Retention	SNK-P0046P	1	1U PASSIVE CPU HS FOR INTEL LGA1156
Power Supply	PWS-351-1H	1	1U 350W MULTI OUTPUT 80PLUS GOLD PWS

Optional Parts List

	Part Number	Qty	Description
Cable	CBL-0288L-01	-	IPASS TO 4 SATA 70/60/50/50CM, W/ 70CM SB, RA ,30AWG