



# Smart-UPS On-Line Lithium Ion UPS 230V

Single-phase, double conversion online UPS with Li-Ion batteries and advanced management features



Life Is 

**APC**<sup>®</sup>  
by Schneider Electric

# A UPS developed for availability of your most critical loads under unstable power conditions worldwide

Smart-UPS<sup>®</sup> On-Line provides high-density, double-conversion, online power protection for servers, voice/data networks, medical labs, and light industrial applications. The Smart-UPS On-Line has a rack/tower convertible chassis. Lithium Ion batteries allow for greater performance at higher temperatures and greater overall lifecycle of the UPS. When business-critical systems require runtime in hours, not minutes, Smart-UPS On-Line can be configured with multiple Li-Ion battery packs to meet aggressive runtime demands.

The included PowerChute<sup>™</sup> Business Edition software provides unattended graceful shutdown of network operating systems. The entire Smart-UPS On-Line family provides value to customers with demanding power conditions, including a very wide input voltage window, extremely tight output voltage regulation, frequency regulation, internal bypass, and input power factor correction.



# Total Cost of Ownership decreases up to 53% when using Smart-UPS On-Line Li-Ion UPS solutions.

APC Smart-UPS with Lithium-Ion technology enables IT professionals to **operate more effectively** and **decrease Total Cost of Ownership (TCO)** by minimizing UPS maintenance and offering **remote UPS management** across distributed environments.

- Greater life expectancy - Increase battery lifecycle 2X
- Greater cost savings - Reduce expenses over the lifetime of the UPS compared to UPSs with lead acid batteries
  - € Eliminate cost of replacing batteries every 3-5 years
  - € Eliminate the labor cost of changing the batteries
  - € Eliminate associated costs of shipping and recycling old batteries
  - € Increased life cycle asset management
- Greater temperature tolerance - Excellent battery performance at higher ambient temperatures up to 40°C
- Greater voltage management of the battery discharge cycle
- Greater efficiency in both charge and discharge of the batteries
- Easy installation and handling with lighter external battery packs
- Management options for remote UPS management

# Smart-UPS On-Line Li-ion UPS

Industry-leading power factor and Li-ion batteries maximizing UPS density.



## Features

### High power density

More real power in watts, 0.9 pf

### High-efficiency "green mode"

Achieves 98 percent efficiency, which saves utility and cooling costs without compromising performance or reliability.

**Graphical LCD display with multicolor backlight** Intuitive interface provides detailed and accurate information with ability to configure locally.

### Built-in energy meter

Measures energy use and displays UPS efficiency in various modes of operation for easy energy tracking.

**Intelligent battery management system** Li-ion battery packs are monitored at an individual cell level to manage voltage and temperatures of the set of cells. This allows for the highest level of safety with the Li-ion battery packs. Enhanced battery intelligence also allows the UPS to automatically recognize if a battery pack is installed or other packs are added at a later date and adjust the runtimes for the connected load.

### Lithium Ion battery pack

Provides long life battery power, ability to operate at higher temperatures without degradation of the performance of the battery. Ability to add an additional 4 battery packs, total of 5, to expand runtime.

### Operate without battery

Ability to immediately protect equipment when power returns after a complete discharge of the battery.


**Five-year warranty on UPS and battery pack** Peace of mind with a 5 year warranty.

Life Is On

**APC**<sup>®</sup>  
by Schneider Electric

# Smart-UPS On-Line Li-Ion UPS

Proven performance with the world's largest installed base of single-phase, double-conversion products.



## Features

### Optional network management card with environmental monitoring

Remote monitoring and control of the UPS and the environment via Ethernet connection.

### Switched outlet group(s)

Ability to control a group of output load receptacles independent from the main UPS. Enables :

- Rebooting hung device without cycling the entire UPS
- Sequenced turn ON/OFF
- Shedding of noncritical loads based on a variety of parameters (battery time, runtime remaining, and overload)
- Scheduled time OFF to conserve energy

### Emergency power off

Remote UPS shutoff in the event of a fire or other emergency. The UPS can accept normally open (NO) or normally closed (NC) contacts.

### Flash upgradeable firmware

Allows for field updates of firmware via communication ports or Network Management Card (NMC)

### Built-in automatic and manual bypass

Ensures seamless power to the load even in the event of catastrophic UPS failure.

### Communication ports

Serial, USB, Ethernet, and SmartSlot for network accessory cards.

### Communication protocols

Modbus serial, USB PowerSummary, HTTP, SNMP, and Telnet.

Life Is On

**APC**  
by Schneider Electric

# Smart-UPS On-Line display

Intuitive, easy-to-use LCD provides clear and accurate information in multiple languages.



Backlit screens :  
**Amber:** Indication of condition that requires attention



**Red:** Indication of UPS alarm that requires immediate attention

## Features

### LCD display screen

Accurately provides real-time status updates in your choice of basic or advanced menus.

### UPS status (scrolling)

- Output voltage
- Input voltage
- Output frequency
- Runtime
- Load
- Battery health

### Control

- UPS and outlet group settings
- Bypass control

### Configuration

- Output voltage, frequency
- Language, brightness, contrast
- Alarm volume
- IP address

### Test and diagnostics

- Initiate battery and runtime calibration tests

### About

- UPS serial number, battery part number
- Battery install and suggested replacement dates

Life Is On

**APC**<sup>®</sup>  
by Schneider Electric

# Smart-UPS On-Line Li-Ion Battery Pack

Long life, lighter weight, higher performance, high density



## Features

### Longer lifecycle

Double the life expectancy vs. sealed lead acid batteries

### Lighter weight

1/3 lighter than sealed lead acid battery pack equivalent

### High density

1U rack height, allows more extended run capability in a smaller footprint.

### Battery Management System (BMS)

Dedicated monitoring system to control the energy flow in the battery pack.

### Overvoltage and overtemperature protection at cell level

Provides a higher level of safety

### Overload, short circuit protection, and thermal runaway protection

Provides a higher level of safety

### Dedicated fuse inside of the battery pack

Provides a higher level of safety

### US Certified UL1973

### Cell Certifications

UL1642  
IEC62133  
UN38.3

### 5 Year Warranty

Life Is On

**APC**  
by Schneider Electric

# Product Family

## SKU technical specifications



	SRTL1000RMXLI SRTL1000RMXLI-NC*	SRTL1500RMXLI SRTL1500RMXLI-NC*
<b>Topology</b>	Double Conversion On-Line	
<b>Output</b>		
Output Power Capacity	900 Watts / 1000 VA	1350 Watts / 1500 VA
Nominal Output Voltage	230V	
Output Voltage Distortion	Less than 2% at full load	
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz (auto sensing)	
Waveform Type	Sine wave	
Output Connections	(8) IEC320 C13	
Switched outlet Groups	Yes	
Efficiency at Full Load	>91%	>92%
<b>Input</b>		
Nominal Input Voltage	230V	
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)	
Input Connections	IEC320 C14	
Input voltage range for main operations	160-275V	
<b>Batteries &amp; Runtime</b>		
Battery Type	Lithium-Ion	
Standard Runtime at full load	32min at 900W	19min at 1350W
Replacement Battery	XBP48RM1U-LI	(external Li-Ion battery pack)
<b>Communications &amp; Management</b>		
Interface Port(s)	Serial (RJ45), Smart-Slot, USB	
Available SmartSlot™ Interface Quantity	1	
Control panel	Multi-function LCD status and control console	
Audible Alarm	Audible and visible alarms prioritized by severity	
Emergency Power Off (EPO)	Yes	
*Preinstalled Network Management Card	included with "NC" suffix SKU	
<b>Physical</b>		
<b>UPS</b>		
Net HxWxD	85mm x 432mm x 587mm	85mm x 432mm x 587mm
Rack Height	2U	
Net Weight	13.7kg	13.7kg
Shipping Weight -	21kg	
Shipping HxWxD	445mm x 600mm x 850mm	445mm x 600mm x 850mm
Color	Black	
<b>Lithium Ion External Battery Pack</b>		
Net HxWxD	85mm x 432mm x 510mm	
Rack Height	1U	
Net Weight	12kg	
Shipping Weight -	16.4kg	
Shipping HxWxD	200mm x 600mm x 850mm	
<b>Environmental</b>		
Operating Environment	32 - 104 °F (0 - 40 °C)	
Operating Relative Humidity	0 - 95%	
Operating Elevation	0-10000 feet (0-3000 meters)	
Storage Temperature	-15 to 45 °C (-30 to 70°C without batteries)	
Storage Relative Humidity	0 - 95%	
Storage Elevation	0-50000 feet (0-15000 meters)	
Audible noise at 1 meter from surface of unit	50.0dBA	
Online Thermal Dissipation	400 BTU/hr	450 BTU/hr
<b>Conformance</b>		
Regulatory Approvals	VDE, EAC, CE, RCM, EN/IEC 62040-1	
Standard Warranty	5 years on UPS and 5 years on battery pack repair or replace	

Life Is On

**APC**  
by Schneider Electric