



LG
Life's Good

BX286

Business Projector



Projection System		DLP
Native Resolution		XGA(1024x768)
Brightness(ANSI)		2800
Contrast Ratio(FOFO)		2100:1
Noise	High Brightness	34dB
	Economic	30dB
Uniformity		65%
Color wheel		5 segment (RYGWB)
Projection Lens	Focus	Manual
	Zoom	Fixed lens
Projection Image	Standard	78.6" @1 m
	Throw Ratio	0,626
Lamp	Type	230W
	Life High Brightness	2500 Hrs
	Life Economic	4000 Hrs
General Specification		
Menu Language	Korean/ English/ French/ Spanish/ German/ Italian/ Swedish/ Portuguese/ Chinese Simplified Chinese Traditional/ Russian/ Polish/ Greek/ Turkish/ Hungarian/ Arabic	
Aspect Ratio Control		Native 4:3, Support 16:9
Sound		5Wx1
Dimension (mm)		306x99x224
Weight (kg)		3,1Kg
Power Consumption		295W(Normal), 243W(Eco)
Power Supply		AC 100~240V/ 50/60Hz
Input Signal Compatibility	Digital(DVI,HDMI)	1080p/1080i/720p/576p/480p, up to SXGA+(1400x1050@60Hz)
	RGB	Up to SXGA+(1400x1050@60Hz)
	Component Video	1080p/1080i/720p/576p/576i/480p/480i
	Composite Video	NTSC-M/NTSC 4.43/PAL/PAL-M/PAL-N/SECAM
Input/Output Terminals		
	HDMI	x
	RGB in	x (2)
	RGB Out	x
	Audio in	x
	Audio Out	x
	Composite	x
	Component	x (2,RGB)
	USB	-
	RS232C	x (Mini Din 3pin)
	RJ45	x
Features		
Digital Keystone Correction		x
Auto Source Detection		x
Quick Power on/off		-
Auto Sleep		x
Color Temperature		x
Presentation Timer		x
Lens Shift		-
Brilliant Color™		x
Black Level Control		-
Expert control		x
VIDI™		Uni-Shape(for OSRAM)
3D Ready		x
FMTransmitter		-
USB Control		-
Office file viewer		-
Accessory		
Item	D-Sub/Power cord/CD Manual/Remote control	

<http://nordic.lge.com>

Design and specifications are subject to change without notice

