

All the essentials

The InFocus IN100 series offers all of the essential functions and features presenters need in an affordable, reliable projector. It's easy to use and projects high-quality images every time thanks to the true-to-life colours of Texas Instruments DLP® technology with InFocus BrilliantColor™ implementation.

- 2700 lumens and up to UXGA resolution for stunning presentations
- Multiple computer inputs provide easy ways to connect
- Filter-free design for less maintenance and 24/7 operation
- Compact size and light weight for easy mobility
- High quality design is backed by a 5-year limited warranty



Bright and Brilliant

A high brightness of 2700 lumens means the IN100 series is bright enough in environments with high ambient light. The award-winning InFocus BrilliantColor implementation brings rich, realistic colour to any presentation.

Flexible

The IN100 series offers multiple computer inputs for flexibility in any environment. Both models are compatible with LiteShow III™ wireless adapter, allowing cable-free presentations. The LiteShow III lets users switch presenters in seconds and transmit data, audio, and video over a 91 m range.



Connectivity options

S-Video	3.5 mm audio in
VGA (HD15)	Audio out
Monitor out	Composite Video
RS232	



MODELS

IN102

SVGA
(800 × 600) NATIVE RESOLUTION
2700 LUMENS

IN104

XGA
(1024 × 768) NATIVE RESOLUTION
2700 LUMENS

Compact

The IN100 series is small and lightweight for easy portability from one room or building to the next. It is compact, weighs about 2.3 kg, and comes with a convenient carrying case.

Resolution Options

Choose from native resolution of SVGA for the best price or XGA for better image detail and clarity. Both models offer high resolution of UXGA (1600 × 1200).



SVGA

800 × 600 PIXELS

XGA

1,024 × 768 PIXELS

IN100 (SERIES)

Security

The IN100 series features a Kensington® lock and user PIN for maximum security.

24/7 Non-Stop Projection

All new InFocus DLP projectors are filter-free and are rated for 24/7 operation, resulting in less maintenance and hours of worry-free use.

Optional Accessories

Replacement Lamp IN102 (SP-LAMP-060)
Replacement Lamp IN104 (SP-LAMP-061)
LiteShow III Wireless Adapter (INLITESHOW3)
Security Lock (SEC-LOCK-01)
Cables & Adapters



LiteShow III

For more information, please visit:
www.infocus.com/Accessories.aspx


Warranty

Providing the highest quality products and support is very important to us. The IN100 series of digital projectors come standard with a 5-year limited factory warranty (including parts¹ and labour²), 1-year limited lamp replacement warranty, and 5-year DLP warranty.

For more information, please visit:
www.infocus.com/Support/Warranty.aspx



8.8 in
223 mm



Remote



3.7 in
94 mm

10.4 in
264 mm



InFocus

Bright Ideas Made Brilliant

www.infocus.com

INFOCUS CORPORATE HEADQUARTERS
13190 SW 68th Parkway
Portland, Oregon 97223-8368, USA
Phone: (1) 503-207-4700
Toll Free: (1) 877-388-8385
Fax: (1) 503-207-1937

INTERNATIONAL HEADQUARTERS
4 Teck Lim Road
Singapore 088382
Phone: (65) 6513-9600
Fax: (65) 6238-0535

Specifications*

IN102

IN104

Native Resolution	IN102 – SVGA 800 × 600 IN104 – XGA 1024 × 768
Maximum Resolution	UXGA 1600 × 1200
Display Technology	Texas Instruments DLP .55" LVDS DDP2431 with BrilliantColor
Brightness	2700 ANSI lm (2200 lm Eco Mode)
Lamp Life **	4000 Hrs Eco Mode (3000 Hrs Normal)
Maximum Contrast Ratio	IN102 – 2800:1 Native IN104 – 4000:1 Native
Audible Noise	28 dbA Eco Mode (33 dbA Normal)
Audio	2 W
Computer Compatibility	PC, MAC
Keystone Correction	+/- 30 degrees
Throw Ratio	1.85 ~ 2.04
Zoom Ratio	1.1:1
Projection Distance	4.9 ~ 19.7 ft / 1.5 m ~ 6 m
Number of Colours	16.7 Millions, True Colours
Aspect Ratio	4:3 (Native), 5:4, 16:9, 16:10
Lamp Power	176 W Eco Mode (220 W Normal)
Power Consumption	228 W Eco Mode (288 W Normal), Standby < 1 W
Power Supply	100 ~ 240 Vac, 50/60 Hz
Video Compatibility	SDTV (NTSC, PAL, SECAM, 480i, 576i), ED/HDTV (480p, 576p, 720p, 1080i, 1080p)
Input Sources	VGA (HD15) × 2, S-Video × 1, Composite Video × 1, Audio (3.5 mm) × 1
Output Sources	VGA (HD15) × 1, Audio (3.5 mm) × 1
Control	RS232
Product Weight	5.07 lbs / 2.3 kg
Product Dimensions - W×D×H	10.4 × 8.8 × 3.7 in / 264 × 223 × 94 mm
Product Colour	Black
Shipping Dimensions - W×D×H	7.3 × 11.4 × 15.5 in / 180 × 290 × 390 mm
Shipping Weight	8.37 lbs / 3.8 kg
Maximum Altitude	10,000 ft / 3098 m
Ships with - Accessories	Power Cord, VGA Cable, Carrying Case, Remote, Safety Instructions, CD Quick Start/User Guide
Menu Languages	English, French, German, Italian, Korean, Norwegian, Turkish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Dutch, Polish, Danish, Finnish
Lamp Particle Containment	Tested to larger than 0.8 mm ***
Accessories Warranty	90 Days
Approvals	C-Tick (Australia), NOM (Mexico), CE (Europe), cTUVus (USA & Canada), FCC (USA), S-Mark (Argentina), GOST (Russia), CCC (China), CCC (China Energy Conservation), PSB (Singapore)
Security	Kensington Lock

* Product specifications, terms, and offerings are subject to change at any time without notice.

** Actual lamp life may vary based on the ambient environment and projector usage. Conditions that may affect lamp life include temperature, altitude, and rapidly switching the projector on and off.

*** Tested to contain particles larger than the specified size in any dimension



©2011 InFocus Corporation. All rights reserved. Specifications are subject to change without further notice. InFocus and InFocus Bright Ideas Made Brilliant are either trademarks or registered trademarks of InFocus Corporation in the United States and other countries. DLP, the DLP logo, and the DLP medallion are trademarks of Texas Instruments. All trademarks are used with permission or are for identification purposes only and are the property of their respective companies. ¹Excludes power supply, fans, colour wheel and light tunnel which are covered for three (3) years. ²Labour is covered for three (3) years from date of proof of purchase. InFocus_IN100_DS_EU_09MAR11. Part Number: MMINFOCUS-0204.