

# Clavister Product Specifications

This document details the current line of Clavister products. Use this document to quickly assess the specifications or compare different Clavister products. For detailed information and specific product brochures, visit [www.clavister.com/products](http://www.clavister.com/products).

	Clavister Eagle Series		Clavister Eagle Series		Clavister Wolf Series		Clavister Wolf Series		Clavister Wolf Series	
	E5	E5 Pro	E80	E80 Pro	W20	W20 Pro	W30	W30 Pro	W3	W3 Pro
<b>Performance</b>										
Firewall Performance (RFC2544)	125 Mbps	250 Mbps	2 Gbps	4 Gbps	4 Gbps	6 Gbps	6 Gbps	10 Gbps	4 Gbps	8 Gbps
IPsec VPN Performance	50 Mbps	100 Mbps	0,5 Gbps	1 Gbps	1 Gbps	1,5 Gbps	1,5 Mbps	2 Gbps	250 Mbps	500 Mbps
Maximum Concurrent Connections	5,000	10,000	250,000	500,000	500,000	750,000	750,000	1,000,000	500,000	1,000,000
Concurrent VPN Tunnels (IPsec)	50	100	100	200	500	1,000	1,000	2,000	500	1,000
Ethernet Interfaces	5 x 1GbE (RJ45) switch block + 2 x 1GbE (RJ45)		6 x 1GbE (RJ45)		6 x 1GbE (RJ45)		6 x 1GbE (RJ45)		8 x 1GbE (RJ45)	
Expansion Slot	No		No		No		One (1) slot, supports: 8 x 1GbE (RJ45), 8 x 1GbE (SFP) or 2 x 10GbE (SFP+)		No	
Maximum Users (ARP Entries)	Unrestricted		Unrestricted		Unrestricted		Unrestricted		Unrestricted	
Virtual Interfaces VLAN (802.1Q)	16	32	64	128	256	512	1,024	2,048	256	512
Routing Tables (Virtual Routers)	3	5	5	10	25	50	50	100	10	25
Support for High Availability (HA)	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Hardware Specifications</b>										
Form Factor / Rack Mountable	Desktop / Yes, with included rack mount kit		Desktop / Yes, with included rack mount kit		1U 19" rack mountable / Yes		1U 19" rack mountable / Yes		1U 19" rack mountable / Yes	
Height x Width x Depth	44 mm x 280 mm x 180 mm (1.73 in x 11.02 in x 7.09 in)		44 mm x 280 mm x 180 mm (1.73 in x 11.02 in x 7.09 in)		44 mm x 431 mm x 305 mm (1.73 in x 16.97 in x 12.01 in)		44 mm x 431 mm x 305 mm (1.73 in x 16.97 in x 12.01 in)		44 mm x 440 mm x 440 mm (1.73 in x 17.32 in x 17.32 in)	
Hardware Weight / Package Weight	1,6 kg (3.53 lb) / 2,48 kg (5,47 lb)		1,7 kg (3.75 lb) / 2,6 kg (5,73 lb)		4 kg (8.82 lb) / 7 kg (15.43 lb)		4 kg (8.82 lb) / 7 kg (15.43 lb)		8 kg (17.64 lb) / 10 kg (22.04 lb)	
Humidity	5% to 95% non-condensing		5% to 95% non-condensing		0% to 95% non-condensing		0% to 90% non-condensing		5% to 95% non-condensing	
Operational Temperature	0° to 40° C (32° to 104° F)		5° to 45° C (41° to 113° F)		5° to 45° C (41° to 113° F)		5° to 45° C (41° to 113° F)		0° to 45° C (32° to 113° F)	
Power Supply	90-264VAC, 50-60 Hz		100-240 VAC, 50-60 Hz		100-240VAC, 50-60 Hz		100-240VAC, 50-60 Hz		100-240VAC, 50-60 Hz, cold-swappable	
Typical Consumption (W)/BTU	13 W / 45 BTU		12 W / 41 BTU		37 W / 127 BTU		37 W / 127 BTU		48 W / 164 BTU	

## CLAVISTER®

Clavister AB, Sjöгатan 6 J, SE-891 60 Örnsköldsvik, Sweden  
Phone: +46 (0)660 29 92 00 | [www.clavister.com](http://www.clavister.com)

## Where to Buy

For information about purchasing Clavister products, please contact your local Clavister Sales Representative or contact Clavister Sales direct at [www.clavister.com/about-us/contact-us](http://www.clavister.com/about-us/contact-us).

	Clavister Wolf Series		Clavister Lynx Series		Clavister Virtual Core Series					
	W5	W5 Pro	X8	X8 Pro	V2	V3	V5	V7	V9	V10
<b>Performance</b>										
Firewall Performance (RFC2544)	10 Gbps	20 Gbps	1 Gbps	2 Gbps	300 Mbps	1 Gbps	2 Gbps	3 Gbps	6 Gbps	10 Gbps
IPsec VPN Performance	1,5 Gbps	3 Gbps	70 Mbps	140 Mbps	150 Mbps	5 Mbps	1 Gbps	2 Gbps	3 Gbps	5 Gbps
Maximum Concurrent Connections	2,500,000	5,000,000	100,000	200,000	16,000	64,000	128,000	250,000	512,000	2,000,000
Concurrent VPN Tunnels (IPsec)	2,500	5,000	100	250	25	500	1,000	1,500	3,000	5,000
Ethernet Interfaces	2 x 10GbE (SFP+), 4 x 1GbE (SFP), 6 x 1GbE (RJ45)		4 x 1GbE (RJ45)		Up to 3	Up to 4	Up to 6	Up to 8	Up to 10	Up to 10
Expansion Slot	No		No		n/a	n/a	n/a	n/a	n/a	n/a
Maximum Users (ARP Entries)	Unrestricted		Unrestricted		Unrestricted	Unrestricted	Unrestricted	Unrestricted	Unrestricted	Unrestricted
Virtual Interfaces VLAN (802.1Q)	512	1,024	128	256	8	32	256	512	1,024	2,048
Routing Tables (Virtual Routers)	100	250	5	10	5	25	50	100	200	1,000
Support for High Availability (HA)	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes
<b>Hardware Specifications</b>										
Form Factor	1U 19" rack mountable / Yes		Industrial DIN-mount / No		Software, supported platforms WmVare ESXi, KVM					
Height x Width x Depth	44 mm x 440 mm x 440 mm (1.73 in x 17.32 in x 17.32 in)		170 mm x 60 mm x 147 mm (6.69 in x 2.36 in x 5.79 in)		n/a					
Hardware Weight	8 kg (17.64 lb) / 10 kg (22.04 lb)		1,2 kg (2.65 lb) / 1,8 kg (3,97 lb)		n/a					
Humidity	5% to 95% non-condensing		5% to 95% non-condensing		n/a					
Operational Temperature	0° to 45° C (32° to 113° F)		-20° to 55° C (-4° to 131° F)		n/a					
Power Supply	100-240VAC, 50-60 Hz, hot-swappable		100-240VAC, 50-60 Hz		n/a					
Typical Consumption (W)/BTU	72 W / 246 BTU		21 W / 78 BTU		n/a					

# CLAVISTER®

Clavister AB, Sjöгатan 6 J, SE-891 60 Örnsköldsvik, Sweden  
Phone: +46 (0)660 29 92 00 | [www.clavister.com](http://www.clavister.com)