

Delock Modular Wall Outlet flush mount 2 Port Cat.6 LSA

Description

This network wall outlet by Delock can be installed in-wall or on a back box with 60 mm mounting holes. The LSA blocks can be used with a punch down tool; the horizontal cable feed allows a flexible installation.



Specification

- Connectors:
 - external: 2 x RJ45 jack
 - internal: 2 x LSA block
- Cat.6 specification
- Shielded (STP)
- TIA-568A/B pinout
- Cable diameter up to 0.644 mm (22 - 26 AWG)
- Material: zinc die cast
- Integrated name plate
- Design suitable central plate 50 x 50 mm
- Mounting holes 60 mm
- Colour: pure white RAL 9010
- Dimensions (LxWxH): ca. 80 x 80 x 39 mm

Item no. 86125

EAN: 4043619861255
 Country of origin: China
 Package: • Zip poly bag

Package content

- Modular Wall Outlet
- 2 screws

Images



General

Suitable for conductor gauge: 22 - 26 AWG

Mounting type: in-wall

Interface

External: 2 x RJ45 Jack

Internal: 2 x LSA block

Technical characteristics

Category: Cat.6

Shielding: shielded

Physical characteristics

Housing colour: white

Length: 80 mm

Width: 80 mm

Height: 39.1 mm