



IPC 2U-2412

The **IPC 2U-2412** is the ideal case for a small and cheap server solution. With its excellent quality and finish, Inter-Tech established the basis for a very variable case.

The **IPC 2U-2412** offers the possibility to install maximal twelve 2.5" or 3.5" Hot-Swap, two 2.5" or one 3.5" HDD. The **IPC 2U-2412** has four 80mm fans, which are mounted directly at the back of the drive brackets and ensure a reliable and optimal cooling.

Additional extras like the reusable and perforated slot brackets, the [USB 3.0 connectors](#) and the lid with the snap lock round off the picture.

Specifications

Motherboard	Mini ITX, µATX, ATX, eATX, SSI EEB maximal motherboard size WxD: 305mm x 345mm, 12" x 13,5"
Drive Bays	12x 2.5" or 3.5" Hot-Swap (max. 12G) 1x mounting bracket for 1x 3.5" or 2x 2.5" internal hard drive/s
Front Connectors	USB 3.0: 2
Cooling System	Internal: 4x 80mm (included, Molex connector)
Controls	Power-Button Reset-Button
LED	Power HDD Activity 3x Network Activity Alert Temperature alert
Power Supply	2U Server Power Supply
Material	1.0-1.2mm Steel
Maximum CPU cooler height	65mm
Maximum graphics card length	345mm
Packing Units	Shipping Unit: 1 piece Pallet: 21 pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887118
EAN-Code	4260133126398
Scope of Delivery	Screw Set Assembly tool Mounting brackets for 2HU PSU 4x 80mm fan included Reusable Low Profile slot brackets USB 3.0 as block connector Lid with snap lock S-ATA/SAS Hot-Swap backplane with SFF-8087 socket*
Features	

*The backplane is only compatible with a SAS-Controller with SFF-8087 connector.
To use the backplane with a SATA-Controller, please order the optional SFF8087 cross-over cables (88885237) in right quantity.

Dimensions and Weight

	Cage	Case	Package
Height	89mm	89mm	155mm
Width	433mm	481mm	560mm
Depth	650mm	680mm	830mm

Weight (net): 10.50kg
Weight (gross): 12.72Kg

Power Supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

Without

Certification:

