

Cross Polarised High-Gain LTE Panel Antenna

650 - 960, 1710 - 2170 and 2500 - 2700 MHz Bands

Product code: XPOL-A0002



The antenna provides an innovative and future proof solution for 4G / 3G and 2G networks. It is a unique wall or pole mountable, dual polarised, full LTE band antenna. Incorporating two separately fed ultra wideband elements in a single housing, the antenna is equipped to provide client side MiMo and diversity support for the networks of today and tomorrow.

The weatherproof housing is designed for mast and wall mounting. The antenna has 2 x 5 metres of low loss cable.

This is a cost effective value added product for signal enhancement and ensuring higher throughputs and stable links for subscribers. This will improve subscribers' user experience and increase client retention. It is ideal for any applications using cellular networks (LTE/HSPA/3G/EDGE/GPRS).

Features:

Wall or pole mount. Lightweight Waterproof

Application areas:

Cellular modems Least Cost Routers GSM customer premises equipment

XPOL-A0002_BROC Version 1

www.poynting-europe.com

sales@poynting-europe.com



Product Code:

XPOL-A0002

Electrical:

Gain 8.3 dBi Max Gain @ 650-960 MHz

9.3 dBi Max Gain @ 1710-2170 MHz 8.2 dBi Max Gain @ 2500-2700 MHz

Input Frequency 650 – 960, 1710 – 2170 and 2500 – 2700 MHz Bands

VSWR across operating bands < 2.5:1 Feed power handling 4 W

Input impedance 50 Ohm (nominal)

Polarisation 2 x Linear (Vertical and Horizontal)

Cable 2 x 5m HDF 195 Connector 2 x SMA male

Cable loss 0.35dB/m @900MHz, 0.53dB/m @2000MHz, 0.6dB/m @2500MHz

Mechanical:

Mounting Wall and pole mount

Dimensions (I x w x h) 260 x 260 x 80 mm (without bracket)


Radome Material ABS (halogen free)
Radome Colour RAL 9001 Cream/grey


Flammability Rating UL 94-V0 RoHS Compliant

Environmental:

Operating temperature -20 to +70°C
Environmental Conditions Outdoor/Indoor


VSWR and Gain Plots






Radiation Patterns:









H-Plane (Azimuth)-700MHz


E-Plane (Elevation)-700MHz






H-Plane (Azimuth)-900MHz

E-Plane (Elevation)-900MHz







H-Plane (Azimuth)-1700MHz

E-Plane (Elevation)-1700MHz







H-Plane (Azimuth)-1900MHz




H-Plane (Azimuth)-2100MHz




H-Plane (Azimuth)-2600MHz



E-Plane (Elevation)-1900MHz



E-Plane (Elevation)-2100MHz



E-Plane (Elevation)-2600MHz