

Z-Perform 1000T

Permanent labels

Thermal transfer

Description

Z-Perform 1000T, an uncoated supercalendered thermal transfer paper label stock, produces scannable bar codes and acceptable images when matched with Zebra 2100, 2300 and 3200 ribbons on Zebra thermal transfer printers. The general purpose permanent acrylic based adhesive offers high initial tact and adhesion on corrugated packaging materials for applications of less than three years.

Suggested Applications

- Labelling of packaging materials.e.g. boxes, pallets in logistics applications
- High volume box labelling
- Product identification
- Work in progress labels
- Shipping, picking and receiving labels in warehousing applications

Technical Specifications

	Description	Caliper
Facestock	75gsm white uncoated paper	70 microns
Adhesive	Permanent acrylic based	26 microns
Liner	62gsm Glassine liner	56 microns
	Total	152 microns

Recommended Zebra printers: Desktop, mid-range and high-performance thermal printers

Recommended Zebra Ribbons: 2100, **2300**, 5049, 5319, **3200**

Minimum application temperature: 0°C

Service temperature range: -20°C to 80°C

Recommended storage conditions: One year duration when stored at 0°C to 21°C at 35% to 50% RH

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, order sample roll SAMPLE5147.