



Cat.6A 2x RJ45 wall outlet White, horizontal entry

No.: 25885

Description

- Suitable for both flush mounting , for installation in cable ducts and for surface mounting with enclosed surface box
- Switch program compatible
- Cat.6A 10GbE compatible Class EA Link
- Fully shielded 360°
- 2 RJ45 connectors obliquely downward 45 ° with dust caps
- Cable entry from the right or left , connection via insulation displacement technology LSA / IDC , colour coding according to TIA / EIA 586 A and B
- Colour: white
- 2 year warranty

RJ45 double socket with two 45 ° connectors each with dust cap, design suitable, for flush and duct mounting, and with additional surface-mounted box

Also available: [Cat.6A 2x RJ45 wall outlet White, vertical entry](#)

Technical details

- Connection via insulation displacement technology LSA / IDC, color coding according to TIA / EIA 586 A and B at the back of the can
- For connection cables AWG 22 to 24
- RJ45 connector with 3μ "gold-plated contacts, compatible with IEC 60603-7-5
- Voltage and current strength 125VAC RMS / 1.5A MP, insulation resistance > 1000Mohm @ 500VDC, Dielectric strength 750VAC RMS @ 60 Hz 1 min.
- Business & storage temperature range: 0 ... 70 ° C / -40 ... 85 ° C
- RJ45 Jack Lifetime: approx. 750
- IDC Lifetime: approx. 200