

AXIS T8154 60 W SFP Midspan

For network or fiber installations

AXIS T8154 60 W SFP Midspan is a compact, plug-and-play media converter with PoE. With its integrated power supply, it minimizes the amount of cabling and facilitates installation. AXIS T8154 offers data input through SFP or RJ45, and delivers High PoE 60 W. It works with all Axis network products supporting Power over Ethernet.

- > **SFP slot for fiber**
- > **Integrated midspan**
- > **High PoE 60 W**
- > **Support for all Axis network products**



Data



PoE



AXIS T8154 60 W SFP Midspan

Midspans		General	
Function	Data and power are fed to a network video product through an Ethernet cable Use together with a PoE splitter for a network video product without built-in PoE support	Display and indicators	Port interfaces are located on the front panel PoE LED Power LED
Data rate	10/100/1000 Mbps	Mounting	Wall, shelf or DIN rail ^a
Installation and management	Automatically detects PoE and High PoE-enabled devices and supplies inline power Local LED management display	Operating conditions	Up to 30 W: -10 °C to 55 °C (14 °F to 131 °F) Up to 60 W: -10 °C to 45 °C (14 °F to 113 °F) Humidity max 90% RH (non-condensing)
Data & power		Storage conditions	-20 °C to 70 °C (-4 °F to 158 °F) Humidity max 95% RH (non-condensing)
Power	High Power over Ethernet, max 60 W	Approvals	Safety: IEC/EN/UL 60950-1, KC, CCC, CB, S-Mark, GS Mark per EN 60950-1 EMC: EN 55022 Class A, EN 55032 Class A, EN 61000 3-2, EN 61000 3-3, EN 55024, FCC Part 15 Subpart B Class A, VCCI Class A, RCM AS/NZS CISPR22 Class A, KCC KN32 Class A, KN35, EN 61000-6-1, EN 61000-6-2, EN 50121-4, IEC 62236-4 Environment: RoHS, REACH, WEEE
Input power	AC input voltage: 100 to 240 V AC AC frequency: 50-60 Hz	Dimensions	50 x 80 x 184 mm (2.0 x 3.1 x 7.2 in)
Max. output power	56 V DC (max 60 W)	Weight	517 g (1.1 lb)
Connectors	Shielded RJ45, EIA 568A and 568B SFP slot Power connector C14	Optional accessories	AXIS T91A03 DIN Rail Clip Mains Cable Angle C13-Open 0.5 m AXIS T8611 SFP Module LC.LX AXIS T8612 SFP Module LC.SX AXIS T8613 SFP Module 1000BASE-T For more accessories, see www.axis.com
Wiring	Data provided over pairs 1/2 and 3/6 for 10/100 Ethernet, over all four pairs for Gigabit Ethernet Power over pairs 1/2 (-), 3/6 (+), 4/5 (+) and 7/8 (-)	Warranty	Axis 3-year warranty, see www.axis.com/warranty

a. Sold as optional accessory

Environmental responsibility:

www.axis.com/environmental-responsibility