


PRODUCT BRIEF

Intel® Wireless-AC 9260
5th Generation Intel 802.11ac, Dual Band, 2x2 Wi-Fi + Bluetooth® 5



Intel® Wireless-AC 9260

Ultra Wi-Fi. Ultra Features. Ultra Connected Experience



The Intel® Wireless-AC 9260 adapter supports Bluetooth® 5 and 2x2 802.11ac Wi-Fi including wave 2 features such as 160MHz channels, delivering up to 1.73Gbps¹ and downlink MU-MIMO. These new features deliver a significant increase in user speeds in dense deployments, supporting fast downloads and long battery life compared to legacy 802.11ac devices. Combined with Intel® Core™ processors and exceptional Intel wireless innovations, the Intel® Wireless-AC 9260 can provide Gigabit download speed¹ and dramatically improve your connected experience at home, work, or on the go.

5TH GENERATION INTEL 802.11AC WIRELESS

Faster Speed Better Coverage Larger Capacity

802.11ac, 2x2, Dual Band,
160MHz, MU-MIMO

Intel® Wireless-AC 9260 enables smoother streaming of higher resolution videos, fewer dropped connections, less congestion, and faster speeds farther away from the router, enabling DL MU-MIMO and 160MHz channel use.

When using 160MHz channels, Intel® Wireless-AC 9260 can deliver over 5x faster Wi-Fi speeds (up to 1.73Gbps) than 802.11n and double the speed of legacy 802.11ac².

Downlink MU-MIMO allows an Access Point to simultaneously transmit data to multiple clients and potentially improve overall downlink network capacity by over 3x².

Bluetooth® 5

Bluetooth® 5 provides 4x⁴ range over BT4.2 with the same power, enabling coverage throughout the home. BT5 also doubles the transmit speed for faster transmissions thereby reducing the overall power.⁴ Additionally, BT5 adds new enhanced data broadcasting enabling seamless services such as location-based services and simpler pairing for Bluetooth devices.

Microsoft Windows 10* Ready

Full support for latest Microsoft Windows 10* OS.

Form Factors (M.2 2230 and 1216)

M.2 2230 modules enable system configuration and platform usages flexibility with the use of a standard Key A or E socket for attaching the module.

M.2 1216 modules enable platform design providing savings on motherboard space and BOM.

EXPERIENCE THE INTEL® DIFFERENCE

Worldwide Regulatory Support Intel® Dynamic Regulatory Solution

Enables worldwide regulatory compliance on a single adapter SKU. The Intel® Wireless-AC 9260 detects its location and automatically optimizes the Wi-Fi settings to local regulatory requirements, maximizing performance in each geography, simplifying travel experience and global enterprise procurement. Future regulatory changes are easily managed during the product life cycle.

Wireless Functionality in Pre-boot Environment

Support for Wi-Fi network and BLE HID connectivity in the platform's UEFI (Unified Extensible Firmware Interface) environment during its boot stage. This capability enables use cases like OS recovery over Wi-Fi and BLE-based keyboard and mouse connectivity in this pre-boot environment.

Wirelessly Project to the Big Screen

Watch your 2-in-1 or laptop content instantly without wires on the big HD screen with stunning image clarity and sound using Wi-Fi Miracast*. Stream movies, videos, games, photos, connect with friends, and more—experience it all, bigger and better than ever before.

BUSINESS-CLASS WIRELESS

Intel® vPro™ Technology⁵

Supports Intel's hardware-based security and management features built into Intel® Core™ vPro™ processors and chipsets that enables IT to manage PCs virtually anywhere, anytime while reducing deployment costs, improving security and ROI.

Intel® Active Management Technology⁶

Using integrated platform capabilities and popular third-party management and security applications, Intel® AMT allows IT or managed service providers to better discover, repair, and help protect their networked computing assets. Intel® AMT is a feature of Intel® Core™ processors with Intel® vPro™ technology.

GENERAL

Dimensions (H x W x D)	M.2 2230: 22mm x 30mm x 2.4mm [1.5mm Max (Top Side)/ 0.1mm Max (Bottom Side)] M.2 1216: 12mm x 16mm x 1.67 (+-0.08)mm
Weight	M.2 2230: 2.9 +/- 0.3 g M.2 1216: 0.61 +/- 0.1 g
Antenna Diversity	Supported
Radio ON/OFF Control	Supported
Connector Interface	M.2: PCIe, USB
Operating Temperature (Adapter Shield)	0°C to +80°C
Humidity Non-Operating	50% to 90% RH non-condensing (at temperatures of 25°C to 35°C)
Operating Systems	Microsoft Windows 10*, Linux* (limited feature support), Chrome*
Wi-Fi Alliance	Wi-Fi CERTIFIED* a/b/g/n/ac with wave 2 features, WMM*, WMM-PS*, WPA*, WPA2*, WPS2*, Protected Management Frames, Wi-Fi Miracast* as Source, and Wi-Fi Direct
IEEE WLAN Standard	IEEE 802.11a/b/g/n/ac, 802.11d, 802.11e, 802.11h, 802.11i, 802.11w; 802.11r, 802.11k, 802.11v pending OS support; Fine Timing Measurement based on 802.11REVmc
Roaming ⁷	Supports seamless roaming between access points
Bluetooth®	Bluetooth® 5

SECURITY⁸

Authentication	WPA* and WPA2*, 802.1X (EAP-TLS, TTLS, PEAP,EAP-SIM, EAP-AKA, EAP-AKA')
Authentication Protocols	PAP, CHAP, TLS, MS-CHAP*, MS-CHAPv2
Encryption	64-bit and 128-bit WEP, TKIP, 128-bit AES-CCMP, 128-bit and 256-bit AES-GCMP
Wi-Fi Direct* Encryption and Authentication	WPA2-PSK, AES-CCMP

COMPLIANCE

Regulatory	For a list of country approvals, please contact your local Intel representatives.
US Government	FIPS ⁹ , FISMA
Product Safety	UL, C-UL, CB (IEC 60950-1)

PRODUCT NAME	MODEL NUMBER	VERSION
Intel® Wireless-AC 9260	9260NGW	802.11ac wave 2, 2x2, Bluetooth ⁵ , PCIe, USB, M.2 2230
Intel® Wireless-AC 9260	9260D2WL	802.11ac wave 2, 2x2, Bluetooth ⁵ , PCIe, USB, M.2 1216 LTE Coex



For more information on Intel® Wireless products, visit intel.com/wireless

¹Based on the theoretical maximum bandwidth enabled by 2x2 802.11ac 160MHz implementations. Actual wireless throughput and/or range will vary depending on your specific operating system, hardware and software configurations. Check with your device manufacturer for details.

²802.11ac 160MHz provides 1.73Gbps maximum throughput, 2x more than 802.11ac 80MHz (867Mbps) and 5x more than 802.11n 40MHz (300Mbps) based on industry standards.

³802.11ac downlink MU-MIMO technology allows concurrently serving multiple devices simultaneously, in turn increasing network capacity potentially by over 3x while improving per-user throughput based on industry standards.

⁴Bluetooth⁵ Specifications, <https://www.bluetooth.com/~media/files/specification/bluetooth-5-faq.ashx?la=en>

⁵Intel® vPro™ Technology is sophisticated and requires setup and activation. Availability of features and results will depend upon the setup and configuration of your hardware, software and IT environment. To learn more visit: <http://www.intel.com/technology/vpro>

⁶Requires activation and a system with a corporate network connection, an Intel® AMT-enabled chipset, network hardware and software. For notebooks, Intel® AMT may be unavailable or limited over a host OS-based VPN, when connecting wirelessly, on battery power, sleeping, hibernating or powered off. Results dependent upon hardware, setup & configuration. For more information, visit <http://www.intel.com/technology/platform-technology/intel-amt>

⁷Roaming is supported only within each respective band and mode of access points.

⁸Some security solutions may not be supported by your device operating system and/or by your device manufacturer. Check with your device manufacturer for details on availability.

⁹Microsoft Windows 7*, Microsoft Windows 8.1* and Microsoft Windows 10*.

^{*}The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by [licensee name] is under license.

Software and workloads used in performance tests may have been optimized for performance only on Intel microprocessors. Performance tests, such as SYSmark and MobileMark, are measured using specific computer systems, components, software, operations and functions. Any change to any of those factors may cause the results to vary. You should consult other information and performance tests to assist you in fully evaluating your contemplated purchases, including the performance of that product when combined with other products. For more complete information visit <http://www.intel.com/benchmarks>.

No license (express or implied, by estoppel or otherwise) to any intellectual property rights is granted by this document. Except as provided in Intel's Terms and Conditions of Sale for such products, Intel assumes no liability whatsoever, and Intel disclaims any express or implied warranty, relating to sale and/or use of Intel products including without limitation, liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Intel products are not intended for use in medical, lifesaving, or life sustaining applications. Intel may make changes to specifications and product descriptions at any time, without notice. For the most current product information, please visit <http://www.intel.com/wireless>.

Cost reduction scenarios described are intended as examples of how a given Intel-based product, in the specified circumstances and configurations, may affect future costs and provide cost savings. Circumstances will vary. Intel does not guarantee any costs or cost reduction.

This device has not been authorized as required by the rules of the Federal Communications Commission.

This device is not, and may not be, offered for sale or lease, or sold or leased, until authorization is obtained.

Intel, the Intel logo, and Intel are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and/ or other countries.

*Other names and brands may be claimed as the property of others.

Copyright © 2017 Intel Corporation. All rights reserved.