


TerraWave 2.4/5 GHz 4/6 dBi Mini Quad Ceiling Wi-Fi Antenna with Four RPSMA Connectors and 18" Pigtails


Ventev's TerraWave 2.4/5 GHz 4/6 dBi Mini Quad Ceiling Wi-Fi Antenna is designed to work with 4-Lead MIMO radios functioning in the 802.11n wireless protocol band. It features four dual band antennas in a single unit. This solution allows engineers to simplify deployments by using only one antenna for dual band access points. Every TerraWave antenna is covered by the company's two-year TerraNet warranty program. For questions or to purchase product, contact your Regional Sales Executive at 210-375-8482, 800-851-4965 or sales @terra-wave.com.



Specifications		
Model	M6040060O2D1820	
Frequency Range	2400 ~ 2500 MHz	5150 ~ 5850 MHz
Bandwidth	100 MHz	700 MHz
Gain	4 dBi	6 dBi
Vertical Beamwidth	60°	70°
Horizontal Beamwidth	360°	
VSWR	≤ 2.0	≤ 2.5
Nominal Impedance	50 Ohms	
Polarization	Vertical	
Max Power	2 Watts	
Connector	RPSMA Connectors with 18" Pigtail	
Dimensions	5.4" x 2.9" x 1"	
Weight	0.44 lbs	
Operating Temperature Range	-40°F to +158°F	
Mounting Style	Center Thread Screw	



Vertical Radiation Pattern @ 2.4 GHz



Vertical Radiation Pattern @ 5 GHz

www.ventev.com/infra sales@ventev.com 1-800-851-4965




TerraWave 2.4/5 GHz 4/6 dBi Mini Quad Ceiling Wi-Fi Antenna with Four RPSMA Connectors and 18" Pigtails









www.ventev.com/infra sales@ventev.com 1-800-851-4965