



IPC 4U-4408

The **IPC 4U-4408** is the perfect rack for a low-priced storage system. The excellent quality of the materials combined with superb workmanship establishes the basis for a very variable case.

The **IPC 4U-4408** offers the possibility to mount maximal eight 2.5" or 3.5" Hot-Swap HDDs and one internal 2.5" or 3.5" HDD (by using a 2.5" with 9,5mm height also a 3.5" HDD simultaneously). The **IPC 4U-4408** is equipped with two serial 80mm fans.

Spezifikationen

Motherboard	Mini ITX, µATX, ATX, eATX, SSI EEB max. motherboard size WxD: 305mm x 345mm, 12" x 13.5"
Drive Bays	2.5" or 3.5" Hot-Swap (max. 12G): 8 2.5" or 3.5" internal: 1 ¹
Front Connectors	USB 3.0: 1 USB 2.0: 1
Cooling System	Rear: 2x 80mm (serial, 3Pin with 4Pin connector)
Controls	Power-Button Reset-Button
LED	Power HDD Activity 3x Network Activity 1x Alert
Power Supply	ATX-/Redundant-PSU
Material	1.0-1.2mm steel
Maximum CPU cooler height	80mm/155mm*
Maximum graphics card length	190mm
Packing Units	Shipping Unit: 1 Piece Pallet: 14 Pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887191
EAN-Code	4260133128620
Scope of Delivery	Screw Set Frame for ATX PSUs (fixed) and redundant 4U-PSU Adapter for 2U-PSU + optional 80mm fan bracket Mounting frame for several PSU Mounting tool
Features	Serial 2x 80mm fans Removable drive bays USB 3.0 and USB 2.0 internal as block connector Hot-Swap Backplane with SFF-8087 connector (max. 12G) ² Snap-in cap Mesh-Grid-Front with dust filter

¹simultaneously only if 2.5" drive with max. 9.5 mm height

² The backplane is only compatible with a SAS-Controller with SFF-8087 connector.

To use the backplane with a SATA-Controller, please order the optional SFF8087 cross-over cables (88885237) in right quantity

*depending on the position of the CPU (80mm, if the CPU is under the HDD cage)

Dimensions and Weight

	Cage	Case	Package
Height	178mm	178mm	250mm
Width	433mm	480mm	560mm
Depth	480mm	520mm	640mm

Weight (net): 9.06kg
Weight (gross): 11.32kg

Power Supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 8Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

Certification:

