



# GOAL ZERO YETI<sup>®</sup>200X PORTABLE POWER STATION


The new Yeti 200X delivers 200 watts of lightweight lithium power and the latest fast-charging technology in a compact, ultra-portable design built to take anywhere. Whether headed out for the day or a weekend, you've got the perfect amount of power to keep essential gear charged from door to destination and back again.




TYPE I - AUS/NZ PLUG



TYPE F - E U PLUG



TYPE G - UK PLUG



| What it charges:                | Approximate charge times:   |
|---------------------------------|---|
| Maximum input                   | 2 hrs   |
| Wall charger (5A)               | 4 hrs   |
| 1x GOAL ZERO Nomad 28 Plus      | 11 hrs  |
| 1x GOAL ZERO Boulder 50         | 6 hrs   |
| <b>Battery:</b>                 |   |
| Cell chemistry                  | Li-ion NMC  |
| Pack capacity                   | 187Wh (14.4V, 13Ah)   |
| Single Cell Equivalent Capacity | 52000mAh @ 3.6V   |
| Lifecycles                      | 500 Cycles to 80% capacity (Discharge rate: 1C, Full charge/discharge, Temp: 25C) |
| Shelf-life                      | Charge every 6-8 months   |
| Management system               | MPPT charge controller, low battery protection                                    |
| <b>Input Ports:</b>             |   |
| 8mm Charging port               | (1x) 13-22V, up to 10A (120W max)   |
| USB-C port                      | (1x) 5-20V, up to 3A (60W max)  |

| <b>Output:</b>        |   |
|-----------------------|---|
| USB-A port            | (2x) 5V, up to 2.4A (12W max) each  |
| USB-C PD port         | (1x) 5-20V, up to 3A (60W max) (in/out)   |
| USB-C port            | 5-12V, up to 3.0A (18W max), regulated (output)   |
| 12V car port          | 12V regulated, up to 15A (180W max)   |
| 6mm port              | 12V unregulated, up to 10A (120W max)   |
| 230V AC Inverter      | 230VAC 50Hz, 0.5A (120W, 200W surge)<br>(output, modified sine wave) (Universal or Type I AC outlets) |
| 120V AC Inverter      | 120VAC 60Hz, 1A (120W, 200W surge)<br>(output, modified sine wave)                                    |
| <b>General:</b>       |   |
| Chainable             | no  |
| Weight                | 5.0 lbs (2.26 kg)   |
| Dimensions            | 7.9 x 5.1 x 5.1 in (20 x 13.1 x 13.1 cm)  |
| Operating usage temp. | 32-104 F (0-40 C)   |
| Certs:                | CE FC   |
| Warranty              | 12 months   |