

## So light and bright, it's the ideal travel companion

The InFocus IN1110 and IN1112 are our smallest and lightest projectors. In fact, weighing in at only 2.7 pounds (1.2 kg) and shining up to 2200 lumens, they're our brightest projectors pound-for-pound.

The combination of high brightness, light weight and compact size is ideal for the travelling professional that faces unpredictable environments every day. Whether you're in a brightly lit room or cramped for time and space, the IN1100 series is the ideal display companion.



### MODELS

#### IN1110

XGA  
(1024 × 768)  
2100 lumens  
2.7 lbs (1.2 kg)

#### IN1112

WXGA  
(1280 × 800)  
2200 lumens  
2.7 lbs (1.2 kg)

## Why choose the IN1100 Series?

- Compact and light weight (only 2.7 lbs) for easy travel
- Up to 2200 lumens of brightness to combat any lighting situation
- HDMI input to connect with today's digital devices
- Durable, road-tested design that's built to last
- Widescreen model to match today's laptop screens
- 3D capable so it's ready for whatever content is to come
- 5-year limited warranty for peace of mind



### Connectivity

HDMI 1.3  
VGA (D-Sub HD15)  
S-Video  
Wired remote via USB

## Big Brightness in a Small Package

### Compact and Light

At only 2.7 pounds (1.2 kg), the IN1110/IN1112 is the smallest and lightest InFocus projector. That means it's easy to pack, easy to carry and won't weigh you down.

### Built for the Road

The projector has a recessed lens and tethered lens cap to keep it safe from impact. Plus, its smooth exterior leaves nothing to snag or break off when taking it in and out of its case. The IN1100 series' durability is backed by our exclusive 5-year limited warranty.

### Widescreen

WXGA resolution and an HDMI connection are must-haves for displaying HD content. The InFocus IN1112 has native WXGA resolution, so your audience will see your widescreen laptop as you intend, without scaling.

### Brightness Adds Confidence

When you're travelling, you can't always control the lighting conditions of where you're presenting. These powerful projectors pump out up to 2200 lumens, so you know your presentation will be sharp and clear regardless of your room's ambient light.

### Connect Fast

In a hurry? HDMI and VGA ports let you connect and present in seconds. An audio out port is also included to connect to an external audio system.

### No projector screen? No problem.

Because a projector screen won't always be available, the Preset button on top of the projector lets you choose a mode that will give you the best image on a beige wall, whiteboard, blackboard, or other surface.

# Preliminary Specifications\*

IN1110

IN1112

Native Resolution	IN1110 – XGA 1024 × 768 IN1112 – WXGA 1280 × 800
Maximum Input Resolution	WUXGA <sup>^</sup> (1920 × 1200)
Display Technology	DLP <sup>®</sup>
Brightness	IN1110 – 2100 ANSI lm (1550 lm Eco Mode) IN1112 – 2200 ANSI lm (1650 lm Eco Mode)
Lamp Life**	4000 Hrs Eco Mode (3000 Hrs Normal)
Contrast Ratio	2600:1
Audio	1 W
Input Connections	VGA (HD15) × 1, HDMI with audio × 1, S-Video × 1, Audio in 3.5 mm × 1
Output Connections	Audio out 3.5 mm × 1
Control	USB mini-B
Aspect Ratio	IN1110 – Native 4:3 (Supports 5:4, 16:9, 16:10) IN1112 – Native 16:10 (Supports 4:3, 5:4, 16:9)
Lamp Power	165 W
Power Consumption	Bright: 185 W Eco: 164 W Standby: <1 W
Power Supply	90 – 264 Vac, 50/60 Hz
Video Compatibility	NTSC/NTSC4.43/PAL/PAL-M/PAL-N/SECAM, 480i/p, 576i/p, 720p, 1080i/p
Synch - Horizontal Scan Freq	31.4 - 91.1 KHz
- Vertical Scan Freq	23.5 - 85 Hz, 120 Hz (3D)
Throw Ratio	IN1110 – 1.95 - 2.15
(distance/image width)	IN1112 – 1.55 - 1.7
Zoom Ratio	1.1:1
Projection Distance	3.9 - 39 ft / 1.2 - 12 m
Image Size (width)	IN1110 – 22 - 242 in IN1112 – 28 - 304 in
Image Offset	IN1110 – 115% IN1112 – 112%
Projection Methods	Front, Rear
Keystone Correction	Automatic, vertical ± 30%
Audible Noise	29 dBA Eco Mode (33 dBA High Power)
Operating Temperature	5° C to 35° C
Maximum Altitude	10,000 ft
Product Color	Black
Product Weight	2.7 lbs / 1.2 kg
Product Dimensions - W×D×H	8.4 × 7.1 × 2.5 in / 213 × 181 × 65 mm
Shipping Weight	7.5 lbs / 3.4 kg
Shipping Dimensions - W×D×H	7.28 × 15.55 × 11.42 in / 185 × 395 × 290 mm
Ships with - Accessories	Power Cord, VGA Cable, Remote, USB Cable, Lens Cap with tether, Carry Case
Menu Languages	English, French, Dutch, Italian, Korean, Norwegian, Portuguese, Russian, Spanish, Simplified Chinese, Traditional Chinese, Swedish, Polish, Turkish, Danish, Finnish
Lamp Rupture Containment	Tested to contain particles larger than 0.8 mm***
Accessory Warranty	90 days
Approvals	FCC (USA), cTUVus (USA and Canada), WEEE (European Union), C-Tick mark (Australia), S-Mark (Argentina), NOM (Mexico), CE (Europe), Gost (Russian), CECP/CCC (China)
Security	Kensington Lock

\* Product specifications, terms, and offerings are preliminary and subject to change at any time without notice.

\*\* Actual lamp life may vary based on the ambient environment and projector usage. Conditions that may affect lamp life include temperature, altitude, and rapidly switching the projector on and off.

\*\*\* Tested to contain particles larger than the specified size in any dimension.

<sup>^</sup> Reduced blanking.

## 3D Capable

Display 3D video and images created in the top emerging 3D standards.

## Optional Accessories

Replacement lamp (SP-LAMP-043)

Presenter RF Remote with USB Receiver (HW-PRESENTER-RF-R)

Pull Up 60 in. Projector Screen (SC-PU-60)

Security Lock (SEC-LOCK-01)

Extended Warranties

For more information, please visit:  
[www.infocus.com/Accessories.aspx](http://www.infocus.com/Accessories.aspx)

## Warranty

The IN1110 and IN1112 projector come standard with a 5-year limited factory warranty (including parts<sup>1</sup> and labor<sup>2</sup>) and a 6-month limited lamp replacement warranty. Extended product and lamp warranty programs are also available.

For more information, please visit:  
[www.infocus.com/Support/Warranty.aspx](http://www.infocus.com/Support/Warranty.aspx)

