

Voxicon VXD-040WUHD-P

SPECIFICATION SHEET




High fidelity 5K 65W monitor

With this top of the line curved display panel, an extra thin bezel and a wide range of features, this monitor will be the center of attention in your working or entertainment space.



2 years of warranty

We provide our customers with a 2-year warranty program. Our policy is "Solve the problem, then ask questions".




5120x2160 resolution

Imagine two high quality QHD monitors right next to one another but without the disruptive bezel in between.



75Hz refresh rate

A 75Hz and Adaptive Sync enabled panel means that you'll get an extra crisp viewing experience with little to no screen tearing.



R2200 curvature

A perfect curvature for office work, due to its thin casing and mounting capability.

Specifications

Panel

| | |
|------------------------|-----------------------|
| SIZE | 40" |
| ACTIVE AREA (HxW) | 929.28 x 392.04 mm |
| ASPECT RATIO | 21:9 |
| RESOLUTION | 5120x2160 |
| REFRESH RATE | 75Hz |
| PANEL TECHNOLOGY | IPS |
| BACKLIGHT TYPE | LED |
| BACKLIGHT POSITION | Side-entry, top |
| BACKLIGHT AMOUNT | 15S4P x 2CN |
| SCREEN COATING | Anti-glare (25%, 3H) |
| G2G RESPONSE TIME (OD) | 6 |
| G2G RESPONSE TIME | 14 |
| PIXEL PITCH (HxW) | 0.1815 x 0.1815 mm |
| PIXELS PER INCH (PPI) | 139 |
| MAXIMUM BRIGHTNESS | 300 cd/m ² |
| MINIMUM BRIGHTNESS | N/A |
| COLOR DEPTH | 1.07B |
| COLOR BIT | 10 bit (8 bit + FRC) |
| COLOR GAMUT | 95% sRGB |
| CONTRAST RATIO | 1000:1 |
| VIEWING ANGLE (HxW) | 178° x 178° |
| CURVATURE | R2200 |

Interfaces

| | |
|------------------|-------------------|
| HDMI | 1x 2.0 (HDCP 2.3) |
| MINI-HDMI | N/A |
| DISPLAYPORT | 1x 1.4 (HDCP 2.3) |
| MINI-DISPLAYPORT | N/A |
| DVI-D | N/A |
| VGA | N/A |
| USB-C | 1x 5Gbps 90W |
| USB-A | 2x 480Mbps |
| USB-B | 1x 480Mbps |
| AUDIO OUT | 1x |

Power

| | |
|-----------------------------|-------------|
| POWER CONSUMPTION (MAX.) | 150W |
| POWER CONSUMPTION (TYPICAL) | 53W |
| STAND-BY POWER | < 0.5W |
| POWER TYPE | DC24V/6.25A |

Features

| | |
|--------------------------|----------|
| FLICKER FREE | Yes |
| LOW BLUE LIGHT | Yes |
| OVERDRIVE | Yes |
| HDR | HDR10 |
| FREESYNC | 48-75 Hz |
| G-SYNC | 48-75 Hz |
| ADAPTIVE SYNC | 48-75 Hz |
| PICTURE-IN-PICTURE (PIP) | Yes |
| PICTURE-BY-PICTURE (PBP) | Yes |
| MPRT | N/A |
| BUILT-IN KVM SWITCH | N/A |
| G2G RESPONSE TIME | N/A |
| DPMS | N/A |
| SPEAKERS | 2 x 3W |

Physical

| | |
|-----------------|---|
| VESA MOUNT | 100 x 100 mm |
| KENSINGTON LOCK | Yes |
| TILT | +5° to -45° |
| SWIVEL | +45° to -45° |
| PIVOT | N/A |
| ELEVATION | 150 mm |
| QUICK RELEASE | Yes |
| WEIGHT (PANEL) | 5890 g |
| WEIGHT (MOUNT) | 4100 g |
| COLOUR | Black |
| PACKAGE SIZE | 1120 x 530 x 165 mm |
| IN THE BOX | USB-C cable, USB-B cable, HDMI cable, Power supply, Power cable, User manual |
| CERTIFICATIONS | CE, ERP |