

Voxicon D32QOEF

SPECIFICATION SHEET




For a higher quality office space

A Quad HD, 31.5" monitor with an IPS panel will ensure a fantastic readability of your documents without sacrificing quality. Our D32QOEF model is the right product for the right price.



2 years of warranty

We provide our customers with a 2-year warranty program. Our policy is "Solve the problem, then ask questions".



2560x1440 resolution

QHD and 31.5" ensures that you'll always have very clear readability of your documents.



60Hz refresh rate

The industry standard of refresh rate for monitors. With 60Hz you'll be able to use this monitor day in, day out.



1.07 billion color depth

No matter the scenario, you'll be enjoying a high-fidelity picture quality.

Specifications

Panel

SIZE	31.5"
ACTIVE AREA (HxW)	698.112 x 392.668 mm
ASPECT RATIO	16:9
RESOLUTION	2560 x 1440
REFRESH RATE	60 Hz
PANEL TECHNOLOGY	IPS
BACKLIGHT TYPE	ELED
BACKLIGHT POSITION	Edge lit
BACKLIGHT AMOUNT	90 lights
SCREEN COATING	Matte
G2G RESPONSE TIME (OD)	6.5
G2G RESPONSE TIME	8
PIXEL PITCH (HxW)	0.2727 x 0.2727 mm
PIXELS PER INCH (PPI)	101.14
MAXIMUM BRIGHTNESS	300 cd/m ²
MINIMUM BRIGHTNESS	250
COLOR DEPTH	1.07B
COLOR BIT	10 bit (8 bit + FRC)
COLOR GAMUT	72% NTSC
CONTRAST RATIO	1200:1
VIEWING ANGLE (HxW)	178° x 178°
CURVATURE	N/A

Interfaces

HDMI	2x 1.4 (HDCP 1.4)
MINI-HDMI	N/A
DISPLAYPORT	1x 1.2
MINI-DISPLAYPORT	1x 1.2
DVI-D	N/A
VGA	1x
USB-C	N/A
USB-A	N/A
USB-B	N/A
AUDIO OUT	1x

Power

POWER CONSUMPTION (MAX.)	54W
POWER CONSUMPTION (TYPICAL)	43W
STAND-BY POWER	< 0.5W
POWER TYPE	DC12V/4.5A

Features

FLICKER FREE	Yes
LOW BLUE LIGHT	Yes
OVERDRIVE	Yes
HDR	TODD
FREESYNC	48-75 Hz
G-SYNC	48-75 Hz
ADAPTIVE SYNC	48-75 Hz
PICTURE-IN-PICTURE (PIP)	N/A
PICTURE-BY-PICTURE (PBP)	N/A
MPRT	N/A
BUILT-IN KVM SWITCH	N/A
DPMS	N/A
SPEAKERS	N/A

Physical

VESA MOUNT	100 x 100 mm
KENSINGTON LOCK	N/A
TILT	+20° to -5°
SWIVEL	+45° to -45°
PIVOT	+90° to -90°
ELEVATION	130mm
QUICK RELEASE	Yes
WEIGHT (PANEL)	5950 g
WEIGHT (MOUNT)	900 g
COLOUR	Black
PACKAGE SIZE	825 x 215 x 550 mm
IN THE BOX	Power supply, Power cable, User manual
CERTIFICATIONS	CE